

C

2



2CSC400408F0201



2CSC400409F0201



2CSC400412F0201



### S 200 C characteristic

Function: protection and control of the circuits against overloads and short-circuits; protection for resistive and inductive loads with low inrush current.

Applications: residential, commercial and industrial.

Standard: IEC/EN 60898, IEC/EN 60947-2

I<sub>cn</sub>=6 kA

Number of poles	Rated current In A	Order details Type code	Order code	Bbn 4016779	Price 1 piece	Price group	Weight 1 piece kg	Pack unit pc.
1	0.5	S 201-C 0.5	2CDS 251 001 R0984	52329 5			0.125	10
	1	S 201-C 1	2CDS 251 001 R0014	52331 8			0.125	10
	1.6	S 201-C 1.6	2CDS 251 001 R0974	52330 1			0.125	10
	2	S 201-C 2	2CDS 251 001 R0024	52332 5			0.125	10
	3	S 201-C 3	2CDS 251 001 R0034	52333 2			0.125	10
	4	S 201-C 4	2CDS 251 001 R0044	52334 9			0.125	10
	6	S 201-C 6	2CDS 251 001 R0064	46400 0			0.125	10
	8	S 201-C 8	2CDS 251 001 R0084	46410 9			0.125	10
	10	S 201-C 10	2CDS 251 001 R0104	46420 8			0.125	10
	13	S 201-C 13	2CDS 251 001 R0134	46430 7			0.125	10
	16	S 201-C 16	2CDS 251 001 R0164	46440 6			0.125	10
	20 ①	S 201-C 20	2CDS 251 001 R0204	46450 5			0.125	10
	25	S 201-C 25	2CDS 251 001 R0254	46460 4			0.125	10
	32 ②	S 201-C 32	2CDS 251 001 R0324	46470 3			0.125	10
	40 ③	S 201-C 40	2CDS 251 001 R0404	46480 2			0.125	10
	50	S 201-C 50	2CDS 251 001 R0504	55100 7			0.125	10
63	S 201-C 63	2CDS 251 001 R0634	55101 4			0.125	10	
2	0.5	S 202-C 0.5	2CDS 252 001 R0984	52335 6			0.250	5
	1	S 202-C 1	2CDS 252 001 R0014	52336 3			0.250	5
	1.6	S 202-C 1.6	2CDS 252 001 R0974	52337 0			0.250	5
	2	S 202-C 2	2CDS 252 001 R0024	52338 7			0.250	5
	3	S 202-C 3	2CDS 252 001 R0034	52339 4			0.250	5
	4	S 202-C 4	2CDS 252 001 R0044	52340 0			0.250	5
	6	S 202-C 6	2CDS 252 001 R0064	46550 2			0.250	5
	8	S 202-C 8	2CDS 252 001 R0084	46560 1			0.250	5
	10	S 202-C 10	2CDS 252 001 R0104	46570 0			0.250	5
	13	S 202-C 13	2CDS 252 001 R0134	46580 9			0.250	5
	16	S 202-C 16	2CDS 252 001 R0164	46590 8			0.250	5
	20	S 202-C 20	2CDS 252 001 R0204	46600 4			0.250	5
	25	S 202-C 25	2CDS 252 001 R0254	46610 3			0.250	5
	32	S 202-C 32	2CDS 252 001 R0324	46620 2			0.250	5
	40	S 202-C 40	2CDS 252 001 R0404	46630 1			0.250	5
	50	S 202-C 50	2CDS 252 001 R0504	55104 5			0.250	5
④ 63	S 202-C 63	2CDS 252 001 R0634	55105 2			0.250	5	
3	0.5	S 203-C 0.5	2CDS 253 001 R0984	52341 7			0.375	1
	1	S 203-C 1	2CDS 253 001 R0014	52342 4			0.375	1
	1.6	S 203-C 1.6	2CDS 253 001 R0974	52343 1			0.375	1
	2	S 203-C 2	2CDS 253 001 R0024	52344 8			0.375	1
	3	S 203-C 3	2CDS 253 001 R0034	52345 5			0.375	1
	4	S 203-C 4	2CDS 253 001 R0044	52346 2			0.375	1
	6	S 203-C 6	2CDS 253 001 R0064	46750 6			0.375	1
	8	S 203-C 8	2CDS 253 001 R0084	46760 5			0.375	1
	10	S 203-C 10	2CDS 253 001 R0104	46780 3			0.375	1
	13	S 203-C 13	2CDS 253 001 R0134	46790 2			0.375	1
	16	S 203-C 16	2CDS 253 001 R0164	46800 8			0.375	1
	20 ①	S 203-C 20	2CDS 253 001 R0204	46810 7			0.375	1
	25	S 203-C 25	2CDS 253 001 R0254	46820 6			0.375	1
	32 ②	S 203-C 32	2CDS 253 001 R0324	46830 5			0.375	1
	40 ③	S 203-C 40	2CDS 253 001 R0404	46840 4			0.375	1
	50	S 203-C 50	2CDS 253 001 R0504	55106 9			0.375	1
④ 63	S 203-C 63	2CDS 253 001 R0634	55107 6			0.375	1	

U<sub>Bmax</sub>  
253 V ~  
72 V ∴

U<sub>Bmax</sub>  
440 V ~  
125 V ∴  
④

U<sub>Bmax</sub>  
440 V ~