

■ SURFACE MOUNTING SOCKET OUTLETS - IP44

EUREKA Series

					522.					512.
					STRAIGHT BOX		ANGLED BOX			
					16A	32A	16A	32A		
Poles	Hz.	Volt	Colour	h.	PG16/M20 □ 10/50	PG21/M25 □ 10/40	PG16/M20 □ 10/50	PG21/M25 □ 10/40		
2P+E	50/60	100-130		4	522.1650	522.3250	512.1650	512.3250		
	50/60	200-250		6	522.1653	522.3253	512.1653	512.3253		
	50/60	380-415		9	522.1658	522.3258	512.1658	512.3258		
	50/60	480-500		7						
	50/60	trasf.		12						
	>300-500	>50		2						
	c.c.	>50-250		3						
	c.c.	>250		8						
3P+E	50/60	100-130		4	522.1651	522.3251	512.1651	512.3251		
	50/60	200-250		9	522.1654	522.3254	512.1654	512.3254		
	50/60	380-415		6	522.1656	522.3256	512.1656	512.3256		
	60	440-460		11						
	50/60	480-500		7						
	50/60	600-690		5						
	50/60	380/440		3						
	100-300	>50		10						
>300-500	>50		2							
3P+N+E	50/60	100-130		4	522.1652	522.3252	512.1652	512.3252		
	50/60	208-250		9	522.1655	522.3255	512.1655	512.3255		
	50/60	346-415		6	522.1657	522.3257	512.1657	512.3257		
	50/60	480-500		7						
	50/60	600-690		5						
	60	440-460		11						

OPTIMA-BASE Series

OPTIMA-TOP Series

513.		513.		SAFE-IN	FAST WIRING	
16A	32A	16A	32A	16A	16A	32A
M20/M25 □ 10/40	M32 □ 1/10	M20/M25 □ 10/40	M32 □ 1/10	M20/M25 □ 10/40	M20/M25 □ 10/40	M32 □ 1/10
513.1650	513.3250	513.1650T	513.3250T	513.1650TH	513.1650TF	513.3250TF
513.1653	513.3253	513.1653T	513.3253T	513.1653TH	513.1653TF	513.3253TF
		513.1658T	513.3258T	513.1658TH	513.1658TF	513.3258TF
		513.16536T	513.32536T			
		513.16533T	513.32533T			
		513.16532T	513.32532T			
		513.16534T	513.32534T			
		513.16538T	513.32538T			
		513.1651T	513.3251T			
		513.1654T	513.3254T	513.1654TH	513.1654TF	513.3254TF
513.1656	513.3256	513.1656T	513.3256T	513.1656TH	513.1656TF	513.3256TF
		513.16565T	513.32565T			
		513.16566T	513.32566T			
		513.16567T	513.32567T			
		513.16564T	513.32564T			
		513.16561T	513.32561T			
		513.16562T	513.32562T			
		513.1652T	513.3252T			
		513.1655T	513.3255T			
513.1657	513.3257	513.1657T	513.3257T	513.1657TH	513.1657TF	513.3257TF
		513.16576T	513.32576T			
		513.16577T	513.32577T			
		513.16575T	513.32575T			
		513.16574T	513.32574T			
		513.16572T	513.32572T			

OPTIMA-BASE Series and OPTIMA-TOP Series IP44:
standard supply cable sleeve

Rated operating voltage >50V
- Approvals: from page 561

Screw terminals
 Spring terminals

■ Versions also available in a metric cable inlet.
For ordering add M after the first three digits
Example: 522.M1650

More information on page 36

