

DOWNLIGHTS

ULTIMUM LED FIRE RATED



ULTIMUM LED FIRE RATED DOWNLIGHT

- Strong padded spring steel retaining springs allows downlight to fit tight to ceiling
- Aluminium heat sink provides excellent heat management for long life
- High initial light output comparable to Halogen for maximum fitting utilisation and low lumen depreciation over time for long LED life
- High efficiency driver compatible with many approved trailing and leading edge dimmers for effective mood or task lighting control
- These fittings meet the requirements of Part B of the Building Regulations and have tested in solid timber construction 30, 60 and 90 minute ceiling types

CONVERSIONS AVAILABLE




ACCESSORIES

RULTRIM-03	ULTIMUM trim, Chrome
RULTRIM-10	ULTIMUM trim, Matte Black
RULTRIM-13	ULTIMUM trim, Brushed Chrome
RLA400DT	LOADPRO 3W Min to 150W Max LED Dimmer

DIMENSIONS (mm)

	Diameter	Depth	Cut-out	Proj
RUL0530-01	85	60	72	3
RUL0540-01	85	60	72	3
RUL0730-01	85	60	72	3
RUL0740-01	85	60	72	3
RUL07X0-01	85	60	72	3
RUL05X0-01	85	60	72	3



DOWNLIGHTS


ULTIMUM LED FIRE RATED



	RUL0530-01	RUL0540-01	RUL0730-01	RUL0740-01
Comparable to:	50W mains	50W mains	50W LV halogen	50W LV halogen
Total Power (W):	4.7	4.7	6.7	6.7
Total Light Output (lm):	410	440	630	660
Efficacy (lm/cctW):	87	94	94	99
Lifetime (hrs):	30,000	30,000	30,000	30,000
Beam Angle (deg):	60	60	60	60
Lux at 1m (lux):	390	420	750	770
CCT (K)	3000	4000	3000	4000
CRI:	80	80	80	80
Power Factor (PF):	0.9	0.9	0.9	0.9
Box Qty:	1	1	1	1
Weight (kg)	0.24	0.24	0.24	0.24

CCT3 COLOUR SELECTABLE

	RUL05X0-01	RUL07X0-01
Comparable to:	50W LV halogen	50W main
Total Power (W):	4.7/4.6/4.9	6.8/6.6/6.8
Total Light Output (lm):	400/450/420	520/610/550
Efficacy (lm/cctW):	86/99/88	77/94/83
Lifetime (hrs):	30,000	30,000
Beam Angle (deg):	60	60
Lux at 1m (lux):	280/310/290	670/700/570
CCT (K)	3000/4000/6000	3000/4000/6000
CRI:	80	80
Power Factor (PF):	0.9	0.9
Box Qty:	1	1
Weight (kg)	0.24	0.24



Triple E Registered