

COMMERCIAL

VULCAN LED CORROSION PROOF – 4FT AND 2FT



VULCAN LED corrosion proof, White


- Suitable for workshops, garages, warehouses, car parks, farm buildings, wet areas
- LED replacement for single and double 18W and 36W fluorescent corrosion proof fittings
- 50,000 hour rated LED life
- IP65, can be used for external applications
- Complete with anti-corrosion clips
- Impact rating of IK08
- High efficacy of 122-126lm/W
- Wide operating ambient temperature range of -25°C to +40°C
- 1-10V dimmable and integral Microwave Sensor options available
- Complies with requirements of the Energy Technology Criteria List. Enhanced Capital Allowances may be claimed on the cost of the luminaires, installation and transport to site
- This product can be customised by our Customised Conversions Department





ROBUS Headquarters, Dublin, Ireland

	Single	Double	Single	Double
	1.2M	1.2M	0.6M	0.6M
Cool White	1 x 24W	2 x 24W	1 x 12W	2 x 12W
Standard	RVUF244FT-24	RVUF484FT-24	RVUF122FT-24	RVUF242FT-24
Emergency	RVUF244FTE-24	RVUF484FTE-24	RVUF122FTE-24	RVUF242FTE-24
Comparable to:	1x36W T8 Fluorescent	2x36W T8 Fluorescent	1x18W T8 Fluorescent	2x18W T8 Fluorescent
Total Power (W):	23.1	47.5	12.8	23.6
Total Light Output (lm):	2,900 standard 330 emergency	5,780 standard 330 emergency	1,600 standard 330 emergency	2,880 standard 330 emergency
Efficacy (lm/cctW):	126	122	126	122
Lifetime (hrs):	50,000	50,000	50,000	50,000
Lux at 1m (lux):	970	1,980	520	950
Beam Angle (deg):	115	115	115	115
CCT (K):	5000	5000	5000	5000
CRI:	80	80	80	80
IP:	65	65	65	65
Impact Rating (IK):	08	08	08	08
Power Factor (PF):	0.95	0.95	0.95	0.95
Height (mm):	97	97	97	97
Length (mm):	1,258	1,258	660	660
Width (mm):	93	140	93	140
Box Qty:	1	1	1	1
Weight (kg):	2.5	3.0	1.1	1.4



ECA eligible