

# LIGHTING CONTROLS

## EXTERNAL PIRS



### PROTON MULTI-DIRECTIONAL 180° PIR, IP65

- Manual over ride with automatic reset after 8 hours
- Passive infra red ensures light is switched on when sensor detects movement of heat, switched off when area is vacated. Minimises false / unwanted triggering
- Large terminals accept 2 x 1.5mm<sup>2</sup> conductors in each terminal. Facility for loop in loop out
- 3 wire - multiple sensors can be wired in parallel
- High load contact rating, allows numerous fittings to be switched
- No minimum load requirements
- Complete with accessory shield to reduce detection angle

#### ACCESSORIES

RPRBRK-01	Corner mount accessory, white
RPRBRK-04	Corner mount accessory, black

#### DIMENSIONS (mm)

	Height	Width	Depth
RPR180PIR-01	51	80	118
RPR180PIR-04	51	80	118

White	<b>RPR180PIR-01</b>
Black	<b>RPR180PIR-04</b>
<b>Detection Area:</b>	180°
<b>Motion Detection Range:</b>	12m diameter at 2.5m
<b>Loading:</b>	Max 300W fluorescent Max 300W LED Max 1,200W incandescent
<b>Time Settings:</b>	10 sec to 15 minutes adjustable
<b>Lux Settings:</b>	3-2000lx
<b>Weight (kg):</b>	0.16
<b>Box Qty:</b>	1



