

OUTDOOR

REMY LED FLOOD LIGHT




REMY LED flood light

- Pre-drilled, angled mounting bracket for fast and simple installation
- No warm up or cool down period required by LED
- Wide operating ambient temperature range of -20°C to 40°C
- Suitable for switching by external PIR, Microwave or Photocell
- Manual override function on PIR
- 600mm arm accessory for use with 10W, 20W and 30W allows projected illumination for signage and other display purposes

ACCESSORIES

RMCSPIKE-04	Garden spike attachment
R10FSA-01	LED flood light signage arm, white
R10FSA-01	LED flood light signage arm, black
RFSB-04	LED flood light swivel bracket, black

DIMENSIONS (mm)	Width	Height	Depth
RRE1030 / PIR	148/148	150/200	73/90
RRE2030 / PIR	148/148	150/200	73/90
RRE3030 / PIR	173/173	170/233	85/96
RRE5030 / PIR	225/NA	220/NA	85/NA



REMY LED
FLOOD LIGHT



Standard Black	RRE1030-04 RRE1040-04	RRE2030-04 RRE2040-04	RRE3030-04 RRE3040-04	RRE5030-04 RRE5040-04
Standard White	RRE1040-01	RRE2040-01	RRE3040-01	RRE5040-01
PIR Black	RRE1030P-04 RRE1040P-04	RRE2040P-04	RRE3040P-04	N/A
PIR White	RRE1040P-01	RRE2040P-01	RRE3040P-01	N/A
Comparable to MH (W):	20	35	50	80
Total Power (W):	9.7/9.6	19.7/19.6	28.9/28.7	46.6/46.7
Total Light Output (lm):	800/880	1,550/1,730	2,530/2,750	4,020/4,670
Efficacy (lm/cctW):	82/92	79/90	87/96	86/100
Lifetime (hrs):	30,000	30,000	30,000	30,000
Beam Angle (deg):	100	100	100	100
Lux at 1m (lux):	340/370	710/780	1,110/1,200	1,660/1,900
CCT (K):	3000/4000	3000/4000	3000/4000	3000/4000
CRI:	80	80	80	80
Power Factor (PF):	0.95/0.5	0.95/0.5	0.95	0.95
Impact Rating (IK):	07	07	07	07
Box Qty:	1	1	1	1
Weight (Kg):	0.49/0.6	0.63/0.7	0.83/0.9	1.1/NA



SEAI Approved

Time off delay:	10s - 10min
Lux settings:	10 - 2,000 lx
Mounting height range:	2.5 - 4m Max
Detection range:	7 - 10m Max
Detection angle:	120°
IP:	65