

KITCHEN & FURNITURE

SPEAR CCT2 LED STRIPLIGHTS



SPEAR CCT2 LED LINKABLE STRIPLIGHT


- Suitable for use in cabinet displays, kitchen wall units, workbench lighting, wardrobe lighting, under counter, bed headboard
- Complete kit includes: mounting brackets, 1.8m mains power cord and integrated male/female end butt connectors allowing fast and simple installation
- Link up to 15 fittings with linking cable accessory or by plugging fittings directly together
- Slim profile allowing the fittings to be easily hidden behind pelmet or cornice so only the lighting effect is visible
- Combined 3000K/OFF/4000K selector switch on each fitting
- Wide operating ambient temperature range of -20°C to +40°C

ACCESSORIES

RLSTR250LEAD	Spear Link Lead 250mm
RSLTR500LEAD	Spear Link Lead 500mm
RSLTR1000LEAD	Spear Link Lead 1000mm



DIMENSIONS(mm)	Width	Length	Height
RLEDSTR3X-01	22	275	43
RLEDSTR4X-01	22	395	43
RLEDSTR8X-01	22	520	43
RLEDSTR10X-01	22	620	43
RLEDSTR14X-01	22	815	43





SPEAR CCT2 LED LINKABLE STRIPLIGHT

	RLEDSTR3X-01	RLEDSTR4X-01	RLEDSTR8X-01	RLEDSTR10X-01	RLEDSTR14X-01
Comparable to:	6W T4	8W T4	16W T4	20W T4	30W T4
Total Power (W):	3.3	4.3	6.7	9.4	13.5
Total Light Output (lm):	380/400	520/550	800/850	1090/1160	1570/1670
Efficacy (lm/cctW):	119/125	122/127	120/127	118/123	117/123
Lifetime (hrs):	30,000	30,000	30,000	30,000	30,000
Beam Angle (deg):	120	120	120	120	120
Illuminance at 1m (lux):	80/90	110/120	160/170	220/240	330/350
CCT (K):	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
CRI (Ra):	80	80	80	80	80
Impact Rating (IK):	08	08	08	08	08
Power Factor (PF):	0.55	0.55	0.55	0.6	0.6
Box Qty:	1	1	1	1	1
Weight (kg):	0.1	0.14	0.19	0.23	0.28

