

SURFACE FITTINGS

GOLF LED CCT3 SELECTABLE



GOLF LED CCT3 SELECTABLE

- Suitable for use in commercial offices, retail shops, nursing homes, apartment stairs and corridors, hotel receptions and sports centre changing rooms
- High impact white polycarbonate construction providing protection against accidental or malicious abuse
- Sensor version rated at 150W so can switch a total of 14 x 100W fittings or 9 x 150W fittings so is ideal for corridor and stairway applications
- High efficiency Pro-diffuser allows maximum light transmission, provides low glare, creates even light distribution – no hot spots
- Wide operating ambient temperature range of -20°C to +35°C
- Utilises high quality SMD LED's which provide low power consumption, high efficacy and long rated LED life
- Can be switched by microwave, external PIR and/or photocell


CONVERSIONS AVAILABLE



ACCESSORIES

R282TRIM-03 Polished Chrome Trim

DIMENSIONS(mm)	Diameter	Height
10W	330	118
15W	330	118





GOLF LED CCT3
BRUSHED CHROME TRIM

	10W	15W
Standard	R100LEDCCT3-01	R150LEDCCT3-01
Emergency	R100LEDCCT3E-01	R150LEDCCT3E-01
Microwave Sensor	R100LEDCCT3S-01	R150LEDCCT3S-01
Emergency & Sensor	R100LEDCCT3E-01SEN	R150LEDCCT3E-01S
Comparable to 2D Fluorescent (W):	28W 2D	38W 2D
Total Power (W):	11 / 10.8 / 11	15.8 / 15.2 / 16
Total Light Output (lm):	840 / 990 / 950 standard 180 emergency	1,240 / 1,420 / 1,360 standard 180 emergency
Efficacy (lm / cctW):	76 / 92 / 86	78 / 93 / 85
Lifetime (hrs):	50,000	50,000
Beam Angle (deg):	110	110
Illuminance at 1m (lx):	270 / 310 / 300 standard 60 emergency	390 / 450 / 430 standard 60 emergency
CCT (K):	3000 / 4000 / 6500	3000 / 4000 / 6500
CRI (Ra):	80	80
Power Factor (PF):	0.9	0.9
Impact Rating (IK):	09	09
Box Qty:	1	1
Weight (kg):	1.23 standard 1.63 emergency	1.23 standard 1.63 emergency



OP
220
240



IP
65

PHOTO
METRICS

PART
L1

PART
L2

SEAI Approved