FEATURES AND USES

▲ Ideal for industrial and commercial applications such as factories and warehouses
▲ Suitable replacement for 250W HID floodlight
▲ Driver on board technology
▲ Made from die-cast aluminium and toughened glass
▲ Angled bracket for easy installation
▲ Supplied with 1.5m of power flex
▲ Available in black

FEATURES AND USES

▲ Ideal for industrial and commercial applications such as factories and warehouses
▲ Suitable replacement for 250W HID floodlight
▲ PIR with manual override
▲ PIR adjustable settings: lux, time and sensitivity
▲ PIR detection range of up to 10 metres

▲ IP65 PIR
▲ Driver on board technology
▲ Made from die-cast aluminium and toughened glass
▲ Angled bracket for easy installation
▲ Supplied with 1.5m of power flex
▲ Available in black

Product Code	Wattage	Lumen Output	IK Rating	IP Rating	CCT (K)	Colour Temp	Voltage	Beam Angle	Rated Life
N6055	100W	9000lm	IK08	IP65	4000K	Cool White	AC220V-240V/ 50-60Hz	115°	30,000hrs

Product Code	Wattage	Lumen Output	IK Rating	IP Rating	CCT (K)	Colour Temp	Voltage	Beam Angle	Rated Life
N6057	100W	9000lm	IK08	IP65	4000K	Cool White	AC220V-240V/ 50-60Hz	115°	30,000hrs