

Xpelair Domestic Sensors & Switches



Remote Humidistat XRH
Ref. 21856AW

- Automatically switches On when the relative humidity reaches an adjustable preset point and switches off when the relative humidity drops
- Pullcord override switch
- Fan indicator light
- Surface or recess mounting
- Suitable for ambient temperatures up to 40°C
- Supply voltage 220-240V 50Hz
- Used with: Premier DX180, DX200, DX400, DX100, XIL, CMF, CX10, GX6
- w160 x h86 x d45 mm



LoVolt Remote Humidistat LVH
Ref. 21863AW

- A 12V SELV LoVolt humidistat
- Automatically switches On when the relative humidity reaches an adjustable pre set point and switches Off when the relative humidity drops
- Pullcord override switch
- Fan indicator light
- Surface or recess mounting
- Suitable for ambient temperatures up to 40°C
- Supply voltage 12V SELV
- Used with: Premier LoVolt DX200, LoVolt CF20, LoVolt DX100
- w160 x h86 x d45 mm



Time delay unit DT20B
Ref. 21850AW

- Connected to a switching circuit such as a bathroom lighting
- Provides adjustable run on time delay after the light has been switched Off
- Time adjustable up to 20 minutes
- Surface or recess mounting
- Suitable for ambient temperature up to 40°C
- Supply voltage 200 - 240V 50Hz
- Used with: Premier DX180, DX200, DX400, DX100, XIL, CMF, CX10, LoVolt DX100
- w100 x h86 x d45 mm




Change Over Switch COS
Ref. 90108AW

- Used to select between high and low speed operation
- Surface or recess mounting
- Used with: DX400, DX400T, DX400RS
- w85 x h85mm



Manual Override Switch MOS
Ref. 90199AW

- Switch 1: high/low speed
- Switch2: On/Off (or Off/tricklevent according to fan option selected)
- Surface or recess mounting
- Used with: Premier DX200 and Premier DX400, DX400RS in conjunction with XRH Remote Humidistat.
- w85 x h85mm



Passive Infrared Sensor XPIRA
Ref. 21871AA

- For indoor use
- Automatically switches a fan on when body movement is detected
- Incorporates a delay timer
- Supply voltage 220-240V 50Hz
- Used with: Premier DX200, DX400, DX100, CMF, CX10, GX6
- w86 x h86mm



Timer and Boost Switch TBS
Ref. 90202AW

- Provides switching between humidity control / manual operation
- Provides selection of high / low extract speed
- Surface or recess mounting
- Used with: GX6HT2
- w85 x h85mm



Air Quality Sensor AQS
Ref. 92097AW

- Provides fully automatic control
- Detects contaminants such as cigarette smoke, body odours, toilet odours and cooking smells
- Activates ventilation system when preset threshold level is exceeded
- Can control up to six fans and accessories
- Integral timer adjustable from 3 - 30 mins
- LED status indicator
- Surface or recess mounting
- Supply voltage 220-240V 50Hz
- w210 x h86 x d41mm