

Technical Data Sheet Code 46484

FD220 Round - Rectangular Adaptor 150mm ID










SPECIFICATION DETAILS
The 204x60mm to 150mm diameter Straight Round to Rectangular adapter is manufactured from (white) High Impact Polystyrene. The 220x90mm rectangular end has a minimum free area of 18,545mm² with a female adaptor for connection outside of the System 220 duct. The 150mm diameter round end has a minimum free area of 16,798mm² with a male spigot for connection inside of the System 150 duct.

Fully compliant with SAP Appendix Q Product Characteristics Database recommendations for duct sizes used with both extract and Mechanical Heat Recovery Systems.Manufactured in compliance with Domestic Plastic Ductwork Specification DW/154 and does meet UL94HB flammability standard.

MAX/MIN OPERATING TEMPERATURES + 60°C to - 15°C

PERFORMANCE CURVE



Size:	220mm x 90mm to 150mm Diameter

For use with:	Vortice Ducting

12 Box quantity:

296g Individual Weight:

Colour: White

120 l/s

AIRFLOW	RESISTANCE
8 l/s	0.11 pa
13 l/s	0.18 pa
21 l/s	0.25 pa
30 l/s	0.60 pa
60 l/s	1.70 pa

Vortice Limited **Beeches House** Eastern Avenue **Burton Upon Trent DE13 0BB** Tel: 01283 492949

5.40 pa

Fax: 01283 544121 sales@vortice.ltd.uk www.vortice.ltd.uk