



IU41

Enclosures

1 row boxes 1-5 modules

This range is ideally suited for the installation of individual modular devices. (RCCBs, MCBs, RCBO's, Switch Disconnectors etc).

The range is available without door, with plain door or with glazed door.

Where larger cables need to be accommodated for switch disconnectors etc extra cabling space is provided in the extended height versions.

All boxes from 2-5 modules are fitted with an earth bar as standard and for those with doors the catch can be replaced

with the optional key locking facility.

These enclosures feature:

- Ample wiring space
- Plain or glazed doors
- Optional key lock

For dimensions see page 2.19.

Description	Cat ref. Without door	Cat ref. Plain door	Cat ref. Glazed door
1 Row 1 Module Suitable for 1 Module RCBO	IU41	IU41-D	-
1 Row 2 Modules	IU2	IU2/D	IU2/GD
1 Row 2 Modules Extended Height	IU42*	IU42/D*	-
1 Row 3 Modules	IU3	IU3/D	-
1 Row 4 Modules	IU4	IU4/D	-
1 Row 4 Modules Extended Height	IU44*	IU44/D*	IU44/GD*
1 Row 5 Modules Extended Height	IU45*	-	-

Note: Recommended maximum cable capacity

* extended height = 35mm² all other references = 6mm²

Accessories

Description	Cat ref.
Keylock with 2 keys suitable for all enclosures fitted with door - IU enclosure	IKL1



VC02SW

Meter Box Switch

VC02SW is an enclosed switch disconnecter suitable for meter box applications where an isolating switch between the electricity meter and consumer unit is required.

It benefits from twin cable clamps which have been additionally proven to secure insulated and sheathed meter tails with conductor sizes

ranging from 16-35mm². This unique feature greatly reduces the strain on the switch terminals reducing the likelihood of loose electrical connections.

The anti-tamper screw cap is a unique feature of VC02SW, allowing the supply authority to simply secure the main cover in place following installation. The device can also be locked

in the open/off position with the appropriate Hager accessory.

VC02SW conforms with BS EN 60947-3:2009+A1:2012 which facilitates the installation to comply with BS 7671 IET Wiring Regulations, in particular guidance given in table 53.4.

For dimensions see page 2.19.

Description	Cat ref.
Meter Box Switch	VC02SW