

# NSYPIN126

Internal door for Spacial WM  
encl.H1200xW600 steel, RAL7035.Adjustable  
in depth



## Main

Range	Spacial
Accessory / separate part category	Enclosure accessory
Product or component type	Door
Application	Multi-purpose
Mounting location	Front side Step slide
Range compatibility	Spacial S3D, CRN, S3X enclosures (except with door stop or door switch) Spacial mounting plate on step slides
Device composition	2 mounting uprights 4 fixing brackets 1 door

## Complementary

Material	Sheet steel for door
Colour	All faces : grey RAL 7035
Surface finish	Polyester powder
Lock type	Lock 3 mm double bar
Number of locks	1
Mounting adjustment	Pitch 25 mm (on step slides)
Door type	Internal plain
Door opening	Reversible
Maximum load	30 kg/m <sup>2</sup>
Height	Nominal : 200 mm
Width	Nominal : 600 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.