

Polyester floor-standing enclosures

Specific accessories

Fixing, cable-entry and other accessories

PLAZ **PLAZT**

PB501369-38



PB500194-49



PB500163-29



Characteristics		Canopy	Wall-fixing lugs	Cable-entry plate
		<ul style="list-style-type: none"> It can be installed in all enclosure models. High resistance to impacts, temperature and bad weather. Increases the height (A) of the enclosure by 38 mm, without modifying its width or depth. 	Drilling positions and marks inside the side panels.	<ul style="list-style-type: none"> Easy drilling in specific customised version. Incompatibility with: adapter plates, step slides, internal door and chassis for modular distribution.
Material		Polyester reinforced with fibreglass	Passivated zinc-coated	Polyester reinforced with fibreglass
Colour		RAL 7032 grey*	-	RAL 7032 grey*
Thickness		-	-	40/10° mm
Ingress protection rating		-	-	IP00
Installation		Essential for outdoor use	-	-
Fixing		-	<ul style="list-style-type: none"> Fixing on the sides by 4 or 6 lugs in horizontal position (6 lugs for enclosures with height ≥ 1000 mm) 10 mm fixing distance on the rear of the enclosure plane 	-
Maximum load		-	180 kg	-
Supply		Delivered with the fixings required for installation	Set of 6 lugs and fixings	Delivered with the fixings required for installation
Width (mm)	Depth (mm) (C)	References		
500	320	NSYTJPLA53	NSYFMPLA	NSYECPLAZ53
750	320	NSYTJPLA73		NSYECPLAZ73
1000	320	NSYTJPLA103		NSYECPLAZ103
1250	320	NSYTJPLA123		NSYECPLAZ123
500	420	NSYTJPLA54		NSYECPLAZ54
750	420	NSYTJPLA74		NSYECPLAZ74
1000	420	NSYTJPLA104		NSYECPLAZ104
1250	420	NSYTJPLA124		NSYECPLAZ124

(1) For enclosures with height ≥ 1000 mm, 1 extra lug at the centre of the A-375 side.

* RAL 7035 from 2016.

PLAT **PLAZT**

PB501055-25



PB500191-25



Characteristics		Grille for IP54 instead of IP44	Renovation and anti-graffiti paint	
		1 grille for 500 and 750 mm wide enclosures, 2 grilles for 1000 and 1250 mm wide enclosures. Prevents the entry of dust and provides the enclosure with IP 5X protection at the top. Maintains the possibility of ventilation.	2-component paint system, specially formulated for polyester enclosures. Renews enclosures and allows easy removal of graffiti. Paint composed of: base (80 %) and hardener (20 %).	
Colour		RAL 7032 grey*	RAL 7032 grey	-
Installation		It is installed from the inside in the upper ventilation opening	-	-
Supply		Delivered with G2 M1 standard synthetic filter, see ClimaSys section	1 kg: <input type="checkbox"/> 800 g tin of base paint <input type="checkbox"/> 200 g tin of hardener (Coverage = 5 m ²)	5 kg: <input type="checkbox"/> 4 kg tin of base paint <input type="checkbox"/> 1 kg tin of hardener (Coverage = 25 m ²)
References		NSYCAG125LPF	NSYAUPG1	NSYAUPG5
				NSYAUPGS

* RAL 7035 from 2016.