


Polyester floor-standing enclosures

Specific accessories

Installation accessories



Characteristics		Metallic mounting plate				Insulating mounting plate			
		Plain mounting plate			Telequick mounting plate				
		- Direct installation on M8 inserts at the rear of the enclosure or on step slides for depth adjustment (see page 202). The enclosures with height of ≥ 1000 mm have intermediate impressions for installing mounting plates of a lesser height (M8 inserts, ref. NSYTEX8, to be ordered separately). - In the 2-door enclosures, it is possible to install 1 complete mounting plate or 2 individual mounting plates.			- Grille with 11 x 26 mm drill holes, with a step of 15 x 30 mm, for direct installation, with clip nuts, of all the devices with fixing at 2, 3 or 4 points, by screws with diameters of 3, 4, 5 or 6 mm. - Direct installation on M8 inserts at the rear of the enclosure or on step slides for depth adjustment (see page 202). The enclosures with height of ≥ 1000 mm have intermediate impressions for installing mounting plates of a lesser height (M8 inserts, ref. NSYTEX8, to be ordered separately).			- Direct installation on M8 inserts at the rear of the enclosure or on step slides for depth adjustment (see page 202). The enclosures with height of ≥ 1000 mm have intermediate impressions for installing mounting plates of a lesser height (M8 inserts, ref. NSYTEX8, to be ordered separately). - In the 2-door enclosures, it is possible to install 1 complete mounting plate or 2 individual mounting plates.	
Material		Galvanised sheet-steel			Galvanised sheet-steel			Bakelite	Polyester
Finish		-			-			-	-
Colour		-			-			-	-
Thickness		25/10° mm			-			40/10° mm	40/10° mm up to 700 mm height 50/10° mm from 800 mm height
Maximum load		150 kg/m ²			150 kg/m ²			100 kg/m ²	
Supply		-			-			1 mounting plate	
For enclosure (mm)		Dimensions			Dimensions			References	
Height (A)	Width (B)	H (mm)	Surface (dm ²)	References	E (mm)	D (mm)	Surface (dm ²)	References	
500	500	-	14	NSYPMM55	350	350	13	NSYPMR55	NSYPMB55 NSYPMA55
	750	-	24	NSYPMM75	350	600	23	NSYPMR57	NSYPMB75 NSYPMA75
	1000	437.5	32	NSYPMM510	350	2 x 350	26	2 x NSYPMR55	NSYPMB510 NSYPMA510
	1250	-	38	NSYPMM55 + NSYPMM75	350	350 + 600	36	NSYPMR55 + NSYPMR57	NSYPMB55 + NSYPMB75 NSYPMA55 + NSYPMA75
750	500	-	24	NSYPMM75	600	350	23	NSYPMR75	NSYPMB75 NSYPMA75
	750	-	40	NSYPMM77	600	600	38	NSYPMR77	NSYPMB77 NSYPMA77
	1000	437.5	54	NSYPMM710	600	2 x 350	46	2 x NSYPMR75	NSYPMB710 NSYPMA710
	1250	687.5	70	NSYPMM712	600	350 + 600	61	NSYPMR75 + NSYPMR77	NSYPMB712 NSYPMA712
1000	500	-	33	NSYPMM105	850	350	32	NSYPMR105	NSYPMB105 NSYPMA105
	750	-	55	NSYPMM107	850	600	54	NSYPMR107	NSYPMB107 NSYPMA107
	1000	437.5	74	NSYPMM1010	850	2 x 350	64	2 x NSYPMR105	NSYPMB1010 NSYPMA1010
	1250	687.5	96	NSYPMM1012	850	350 + 600	86	NSYPMR105 + NSYPMR107	NSYPMB1012 NSYPMA1012
1250	500	-	42	NSYPMM125	1100	350	42	NSYPMR125	NSYPMB125 NSYPMA125
	750	-	70	NSYPMM127	1100	600	70	NSYPMR127	NSYPMB127 NSYPMA127
	1000	437.5	96	NSYPMM1210	1100	2 x 350	84	2 x NSYPMR125	NSYPMB1210 NSYPMA1210
	1250	687.5	124	NSYPMM1212	1100	350 + 600	112	NSYPMR125 + NSYPMR127	NSYPMB1212 NSYPMA1212
1500	500	-	51	NSYPMM155	1350	350	51	NSYPMR155	NSYPMB155 -
	750	-	85	NSYPMM157	1350	600	85	NSYPMR157	NSYPMB157 -
	1000	437.5	118	NSYPMM1510	1350	2 x 350	102	2 x NSYPMR155	NSYPMB1510 -
	1250	687.5	152	NSYPMM1512	1350	350 + 600	136	NSYPMR155 + NSYPMR157	NSYPMB1512 -



(1) Reinforcing fold for steel mounting plate **NSYPMM1010** to **NSYPMM1512**.

(2) A-125 for references **NSYPMM1010** to **NSYPMM1512**, A-120 for the polyester mounting plate, ref. **NSYPMA●●●**.

Polyester floor-standing enclosures

Specific accessories

Installation accessories



Side mounting plates			Partial plain mounting plate		Technical uprights		Anti-burglary accessory	
Polyester mounting plates fixed to the sides of the enclosure for additional installations. Installation on the M8 bosses by adding inserts, ref. NSYTEX8 .			Direct fixing on the uprights, with the notched sliding nuts or pivoting nuts, see common accessories section.		- Supports for fixing rails, perforated grilles and plain partial mounting plates. - Details in the common accessory section. - Fixing at the rear on the M8 inserts or on the step slides.		Anti-burglary accessory for polyester outdoor Heavy Duty in accordance with ENV 1627-1630:2011 class 2. It keeps the Insulation Class II according to IEC 61439-1:2011.	
Polyester			Galvanised sheet-steel		Zinc-coated steel		Steel with anti-corrosive coating	
-			-		-		Structured finish, 100 % polyester powder	
-			-		-		RAL 7035 grey	
40/10° mm up to 750 mm height 50/10° mm from 800 mm height			25/10° mm		20/10° mm		-	
100 kg/m²			150 kg/m²		-		-	
Reference by unit. Order by multiples of 2			1 mounting plate		2 technical uprights		1	
References			References		Dimensions (mm)	References	References	
Enclosure depth			247 mm height	397 mm height			Depth 420 mm	Depth 620 mm
320 mm	420 mm	620 mm						
NSYPMLA53	NSYPMLA54	-	-	-	-	-	-	-
NSYPMLA53	NSYPMLA54	-	NSYSPMP2575	-	-	-	-	-
NSYPMLA53	NSYPMLA54	-	NSYSPMP25100	NSYSPMP40100	-	-	-	-
NSYPMLA53	NSYPMLA54	-	-	-	-	-	-	-
NSYPMLA73	NSYPMLA74	NSYPMLA76	-	-	625	NSYTVR7	-	-
NSYPMLA73	NSYPMLA74	-	NSYSPMP2575	-	-	-	NSYBGN774HD	NSYBGN776HD
NSYPMLA73	NSYPMLA74	-	NSYSPMP25100	NSYSPMP40100	-	-	-	-
NSYPMLA73	NSYPMLA74	-	-	-	-	-	-	-
NSYPMLA103	NSYPMLA104	-	-	-	875	NSYTVR10	NSYBGN1054HD	-
NSYPMLA103	NSYPMLA104	-	NSYSPMP2575	-	-	-	NSYBGN1074HD	-
NSYPMLA103	NSYPMLA104	-	NSYSPMP25100	NSYSPMP40100	-	-	-	-
NSYPMLA103	NSYPMLA104	-	-	-	-	-	-	-
NSYPMLA123	NSYPMLA124	NSYPMLA126	-	-	1125	NSYTVR125	NSYBGN1254HD	-
NSYPMLA123	NSYPMLA124	-	NSYSPMP2575	-	-	-	NSYBGN1274HD	NSYBGN1276HD
NSYPMLA123	NSYPMLA124	-	NSYSPMP25100	NSYSPMP40100	-	-	-	-
NSYPMLA123	NSYPMLA124	-	-	-	-	-	NSYBGN12124HD	NSYBGN12126HD
NSYPMLA153	NSYPMLA154	NSYPMLA156	-	-	1375	NSYTVR15	-	-
NSYPMLA153	NSYPMLA154	-	NSYSPMP2575	-	-	-	NSYBGN1574HD	NSYBGN1576HD
NSYPMLA153	NSYPMLA154	-	NSYSPMP25100	NSYSPMP40100	-	-	-	-
NSYPMLA153	NSYPMLA154	-	-	-	-	-	NSYBGN15124HD	NSYBGN15126HD
					Note: enclosures with widths of 1000 and 1250 allow the installation of 4 uprights to integrate 2 mounting plates of 500 mm or of 500 and 750 mm.			

Note: the diagrams above relate to the metal mounting plates. The mounting plates made from insulating material only have 4 or 8 main fixing points and the external dimensions of the diagrams.