



Mounting

Mounting plates for wall-mounting enclosures

S3D S3X PLM



Characteristics		Mounting plates				Plain	Silkscreened	Microperforated	Telequick mounting plate**		
						-	Silkscreened for easier distribution of the products to be installed. Centimetric grid pattern.	They considerably reduce the products installation time thanks to the holes prepared to receive the self-tapping screws. Holes with Ø 3.6 mm in steps of 12.5 mm.	They allow cable guides and ducting and other installation accessories to be clipped on, making it easier to install switchgear. 11 x 26 mm slots. Switchgear fixing by clip-on nuts.		
Material						Galvanised-steel	Galvanised-steel	Galvanised-steel	Zinc-coated-steel		
Colour						-	-	-			
Supply						1 mounting plate without fixing elements			1 mounting plate without fixing elements		
For enclosures (mm)		Dimensions (mm)		Max. load	Surface	References	References	References	No. of perforations in		References
Height	Width	H	W	(kg)	(dm²)				Height	Width	
60	700	-	-	-	-	-	-	-	-	-	-
120	700	-	-	-	-	-	-	-	-	-	-
200	200	150	150	40	2.3	NSYMM22	-	-	-	-	-
	300	150	250	40	3.7	NSYMM23	-	-	-	-	-
250	200	200	150	40	3	NSYMM2520	-	-	-	-	-
	400	200	350	60	7	NSYMM2540	-	-	-	-	-
	500	200	450	60	9	NSYMM2550	-	-	-	-	-
300	150	-	-	-	-	-	-	-	-	-	-
	195	-	-	-	-	-	-	-	-	-	-
	200	250	150	60	3.7	NSYMM32	-	NSYMF32	16	5	NSYMR32
	250	250	200	60	5	NSYMM3025*	-	-	16	8	NSYMR3025
	300	250	250	60	6.3	NSYMM33	-	NSYMF33	16	9	NSYMR33
	400	250	350	60	8.8	NSYMM43*	NSYMS43*	NSYMF43*	18	11	NSYMR34
	450	250	400	60	10	NSYMM3045	-	-	-	-	-
	500	-	-	-	-	-	-	-	-	-	-
	600	250	550	60	13.8	NSYMM36	-	-	-	-	-
	700	-	-	-	-	-	-	-	-	-	-
400	300	-	-	-	-	-	-	-	22	9	NSYMR43
	400	350	350	60	12.3	NSYMM44	NSYMS44	NSYMF44	24	11	NSYMR44
	600	350	550	90	12.3	NSYMM64*	NSYMS64*	-	24	19	NSYMR46
	800	350	750	90	26.3	NSYMM48	-	-	-	-	-
405	300	-	-	-	-	-	-	-	-	-	-
500	300	450	250	60	11.3	NSYMM53*	NSYMS53*	NSYMF53	29	9	NSYMR53
	400	450	350	90	15.8	NSYMM54	NSYMS54	NSYMF54	31	11	NSYMR54
	500	450	450	90	20.3	NSYMM55*	NSYMS55*	NSYMF55	31	14	NSYMR55
600	400	550	350	90	19.3	NSYMM64	NSYMS64	NSYMF64*	38	11	NSYMR64
	500	550	450	90	24.8	NSYMM65	-	NSYMF65	38	14	NSYMR65
	600	550	550	135	30.3	NSYMM66	NSYMS66	NSYMF66	38	17	NSYMR66
	700	-	-	-	-	-	-	-	-	-	-
	800	-	-	-	-	-	-	-	36	24	NSYMR68
700	500	650	450	135	29.3	NSYMM75	NSYMS75	NSYMF75	44	14	NSYMR75
	600	650	550	135	35.8	NSYMM76	-	-	44	17	NSYMR76
705	500	-	-	-	-	-	-	-	-	-	-
795	600	-	-	-	-	-	-	-	-	-	-
800	600	750	550	135	41.3	NSYMM86*	NSYMS86*	NSYMF86*	51	17	NSYMR86
	800	750	750	150	56.3	NSYMM88	-	NSYMF88	51	24	NSYMR88
	1000	-	-	-	-	-	-	-	49	31	NSYMR810
900	500	-	-	-	-	-	-	-	-	-	-
	600	-	-	-	-	-	-	-	-	-	-
	700	-	-	-	-	-	-	-	-	-	-
1000	600	950	550	150	52.3	NSYMM106	-	NSYMF106	64	17	NSYMR106
	800	950	750	150	71.3	NSYMM108*	-	NSYMF108*	64	24	NSYMR108
	1000	950	950	180	90.3	NSYMM1010	-	NSYMF1010	62	31	NSYMR1010
	1200	-	-	-	-	-	-	-	62	37	NSYMR1012
1200	600	1150	550	180	63.3	NSYMM126	-	NSYMF126	75	17	NSYMR126
	800	1150	750	180	86.3	NSYMM128*	-	NSYMF128	75	24	NSYMR128
	1000	1150	950	180	109.3	NSYMM1210*	-	NSYMF1210*	75	31	NSYMR1210
	1200	1150	1150	180	132.3	NSYMM1212	-	-	-	-	-
1400	1000	1350	950	180	128.3	NSYMM1410	-	-	88	31	NSYMR1410

* Plate with reversible dimensions; it can be installed in enclosures with inverted dimensions.

Example: Plate ref. **NSYMM64** can be used for the following enclosures: H 600 x W 400 mm or H 400 x W 600 mm.

For plain and silkscreened mounting plates: In wall-mounting enclosures with widths of 1000 and 1200 mm, it is possible to install 2 mounting plates at different depths using an additional central step slide **NSYSDRSDCR** (more information on page 218).



** To install two mounting plates in a single enclosure, also order reference **NSYCRNGSDR**.
See details on page 218.
To install the plate in an enclosure with 6 studs, also order reference **NSYEMR**.