

Fire Rated MV/LV Downlight - Satin Nickel



The Firestay Non Integrated Downlight gives you the freedom to choose your lamp without the need to replace the complete fitting. Available as Fixed, Centre Tilt & IP65 Showerlight with a choice of finishes and accessories.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist ceiling systems
- Part B/C/E compliant
- Part L compliant with BELL Halo Elite/Halo Glass LED GU10
- Fixed / Centre Tilt / Showerlight IP65 Downlights
- Suitable for 240V lamps (GU10 lamp holder included)

Codes

Commodity Code	94054099
EAN	5013588106618
Luckins Code	406087436

Technical

Volts (V)	240
Cap	GU10
Guarantee	5 Year Guarantee
Frequency (Hz)	50
IP Rating	IP20

Dimensions

Downlight Cut Out (mm)	68
Height	98 mm
Width	93 mm
Length	134 mm
Bell_Depth	94 mm
Diameter	85 mm
Individual Product Weight (no packaging)	0.17 kg

Packaging

Single Carton Weight	0.67 kg
Single Carton Height	7.8 cm
Single Carton Width	10.5 cm
Single Carton Depth	8.9 cm
Outer Box Weight	11 kg
Outer Box Height	41.5 cm
Outer Box Width	46.5 cm
Outer Box Depth	22.5 cm
Outer Box Qty	50
Outer Box CMB	0.043419375