

Switchgear

Enclosed Switch-Disconnectors

3 Pole Enclosed Switch-Disconnectors (IP65)



IEC & EN 60947-3

20mm cable entries up to 40A / 25mm on 63 & 80A / Robust polycarbonate enclosure / UV resistant / Enclosure glow wire flammability rating 960°C / Halogen free / Lower smoke generation Padlockable in the OFF position for added security (For up to 3 padlocks)

All switch ratings at AC-21 - See page 140 for technical data

Part Number	Description	Price	Per
LB323P	32A 3 Pole (Insulated Enclosure)	£20.85	1
LB403P	40A 3 Pole (Insulated Enclosure)	£26.82	1
LB633P	63A 3 Pole (Insulated Enclosure)	£31.08	1
LB803P	80A 3 Pole (Insulated Enclosure)	£34.96	1

3 Pole Metal Clad Enclosed Switch-Disconnectors (IP54)



Will accept 2
Auxiliaries

IEC & EN 60947-3

Padlockable in the OFF position for added security (For up to 3 padlocks)
Cover: RAL 7035 / Base: RAL 7043 /
H:200 x W:145 x D:190mm (134mm Inc. handle)

All switch ratings at AC-21 - See page 140 for technical data

Part Number	Description	Price	Per
LB323PSTB	32A 3 Pole (Metal Clad Enclosure)	£41.37	1
LB633PSTB	63A 3 Pole (Metal Clad Enclosure)	£50.54	1
LB803PSTB	80A 3 Pole (Metal Clad Enclosure)	£57.75	1

3 Pole & 3 Pole + Sw. Neutral Switch-Disconnectors Dimensions (mm)

Part Number	Height (mm)	Width (mm)	Depth (mm)	Depth (Incl. Switch)	Additional Aux. (Ordered Separately)
LB323P	125	100	74	118	1 Auxiliary
LB403P					
LB203PSN					
LB253PSN					
LB323PSN					
LB403PSN	175	125	90	134	2 Auxiliaries (One either side of the switch)
LB633P					
LB803P					
LB633PSN					1 Auxiliary
LB803PSN					
LB1003PSN	280	190	130	190	
LB1253PSN					

3 Pole + Sw. Neutral Enclosed Switch-Disconnectors (IP65)



Early Make / Late Break
Neutral Pole (Page 11)



Neutral contacts must be used when switching the neutral.

IEC & EN 60947-3

20mm cable entries up to 40A / 25mm on 63 - 125A
Robust polycarbonate enclosure / UV Resistant / Enclosure glow wire flammability rating 960°C / Halogen free / Lower smoke generation
Padlockable in the OFF position for up to 3 padlocks

Switch Ratings:

AC-21 20-80A - See page 140 for technical data

AC-22 100A & 125A - See page 141 for technical data

Part Number	Description	Price	Per
LB203PSN	20A 3P Sw. Neutral (Insulated Enclosure)	£17.63	1
LB253PSN	25A 3P Sw. Neutral (Insulated Enclosure)	£20.95	1
LB323PSN	32A 3P Sw. Neutral (Insulated Enclosure)	£22.00	1
LB403PSN	40A 3P Sw. Neutral (Insulated Enclosure)	£29.00	1
LB633PSN	63A 3P Sw. Neutral (Insulated Enclosure)	£31.25	1
LB803PSN	80A 3P Sw. Neutral (Insulated Enclosure)	£37.18	1
LB1003PSN	100A 3P Sw. Neutral (Insulated Enclosure)	£85.36	1
LB1253PSN	125A 3P Sw. Neutral (Insulated Enclosure)	£100.00	1

3 Pole + Sw. Neutral Larger Enclosure Version (IP65)



Early Make / Late Break
Neutral Pole (Page 11)



Neutral contacts must be used when switching the neutral.

IEC & EN 60947-3

25mm cable entries
Robust resilient polycarbonate enclosure / UV resistant
Enclosure glow wire flammability rating 960°C
Padlockable in the OFF position for added security (For up to 3 padlocks)
All switch ratings at AC-21 - See page 140 for technical data

Part Number	Description	Price	Per
LB253PSNBB	25A 3P Sw. Neutral (Insulated Larger Enclosure)	£29.63	1
LB323PSNBB	32A 3P Sw. Neutral (Insulated Larger Enclosure)	£35.48	1
LB403PSNBB	40A 3P Sw. Neutral (Insulated Larger Enclosure)	£39.38	1

3 Pole + Sw. Neutral Larger Enclosure Dimensions (mm)

Height (mm)	Width (mm)	Depth (mm)	Depth (Incl. Switch)	Additional Aux. (Ordered Separately)
175	125	90	134	1 Auxiliary