**NSYCRN****Mild Steel Wall Mounted Enclosures**

Steel enclosures made from a continuous length of sheet steel. Both internally and externally protected with texturized polyester epoxy resin RAL7035 grey paint.


Features and Benefits

- Welded studs on the back for direct fixing of mounting plates and other accessories
- Drill holes for wall fixings are sealed with the supplied plastic plugs to maintain degree of protection
- Concealed and easily removable hinges allow the easy reversal of the door, as well as enabling 120° door opening
- Foamed-in polyurethane gasket and front rain gutter ensures high degree of protection
- IK10
- Suitable for use indoors
- Supplied with a double bar lock as standard



Mild Steel Wall Mounted Enclosure.

TYPE	Height mm	Width mm	Depth mm	IP Rating	Number of doors	Pack Cont.
NSYCRN22150	200	200	150	IP66	1	1
NSYCRN23150	200	300	150	IP66	1	1
NSYCRN252150	250	200	150	IP66	1	1
NSYCRN325150	300	250	150	IP66	1	1
NSYCRN325200	300	250	200	IP66	1	1
NSYCRN33150	300	300	150	IP66	1	1
NSYCRN33200	300	300	200	IP66	1	1
NSYCRN34200	300	400	200	IP66	1	1
NSYCRN345150	300	450	150	IP66	1	1
NSYCRN43150	400	300	150	IP66	1	1
NSYCRN43200	400	300	200	IP66	1	1
NSYCRN44200	400	400	200	IP66	1	1
NSYCRN46250	400	600	250	IP66	1	1
NSYCRN46300	400	600	300	IP66	1	1
NSYCRN54150	500	400	150	IP66	1	1
NSYCRN54200	500	400	200	IP66	1	1
NSYCRN54250	500	400	250	IP66	1	1
NSYCRN55250	500	500	250	IP66	1	1
NSYCRN64150	600	400	150	IP66	1	1
NSYCRN64200	600	400	200	IP66	1	1
NSYCRN64250	600	400	250	IP66	1	1
NSYCRN65150	600	500	150	IP66	1	1
NSYCRN65200	600	500	200	IP66	1	1
NSYCRN65250	600	500	250	IP66	1	1
NSYCRN66200	600	600	200	IP66	1	1
NSYCRN66250	600	600	250	IP66	1	1
NSYCRN66300	600	600	300	IP66	1	1
NSYCRN68300	600	800	300	IP66	1	1
NSYCRN75200	700	500	200	IP66	1	1
NSYCRN75250	700	500	250	IP66	1	1
NSYCRN86200	800	600	200	IP66	1	1



NSYCRN

Mild Steel Wall Mounted Enclosures

TYPE	Height mm	Width mm	Depth mm	IP Rating	Number of doors	Pack Cont.
NSYCRN86250	800	600	250	IP66	1	1
NSYCRN86300	800	600	300	IP66	1	1
NSYCRNG86400*	800	600	400	IP66	1	1
NSYCRN88200	800	800	200	IP66	1	1
NSYCRN88300	800	800	300	IP66	1	1
NSYCRNG810300D*	800	1000	300	IP55	2	1
NSYCRNG812300D*	800	1200	300	IP55	2	1
NSYCRN106250	1000	600	250	IP66	1	1
NSYCRN106300	1000	600	300	IP66	1	1
NSYCRNG106400*	1000	600	400	IP66	1	1
NSYCRN108250	1000	800	250	IP66	1	1
NSYCRN108300	1000	800	300	IP66	1	1
NSYCRNG108400*	1000	800	400	IP66	1	1
NSYCRNG1010300D*	1000	1000	300	IP55	2	1
NSYCRNG1012300D*	1000	1200	300	IP55	2	1
NSYCRNG1012400D*	1000	1200	400	IP55	2	1
NSYCRNG126300*	1200	600	300	IP66	1	1
NSYCRNG126400*	1200	600	400	IP66	1	1
NSYCRNG128300*	1200	800	300	IP66	1	1
NSYCRNG128400*	1200	800	400	IP66	1	1
NSYCRNG1210300D*	1200	1000	300	IP55	2	1
NSYCRNG1210400D*	1200	1000	400	IP55	2	1
NSYCRNG1212300D*	1200	1200	300	IP55	2	1
NSYCRNG1212400D*	1200	1200	400	IP55	2	1
NSYCRNG1410300D*	1400	1000	300	IP55	2	1



* NSYCRNG enclosures supplied with a 3 point locking system