

define® 13A Fused Connection Units

'Ingot' Fused Connection Units with Flex Outlet | 'Ingot' Fused Connection Units without Flex Outlet

Control Switches

'Ingot' Fan Isolation Switches | 'Ingot' 20A Switches with/without Flex Output

define®



550



551



552



520



522



553



750



523



751



752



753



722



723

13A 'Ingot' Fused Connection Units with Flex Outlet

550	13A FCU with Flex Outlet
551	13A FCU DP Switched with Flex Outlet
552	13A FCU DP Switched with Flex Outlet & Neon
553	13A FCU with Flex Outlet And Neon

13A 'Ingot' Fused Connection Units without Flex Outlet

750	13A FCU
751	13A FCU DP Switched
752	13A FCU DP Switched & Neon
753	13A FCU with Neon

Fan Isolation 'Ingot' Switch

520	10A 3 Pole Fan Isolation Switch
This Product Is Not Modular	

20A DP 'Ingot' Switch with Optional Flex Outlet (11mm Dia.)

522	20A DP 'Ingot' Switch with Flex Outlet
523	20A DP 'Ingot' Switch with Flex Outlet & Neon

20A DP 'Ingot' Switch (without Flex Outlet)

722	20A DP 'Ingot' Switch
723	20A DP 'Ingot' Switch with Neon

3 Pole And 20A DP Switches Are Non-Modular

Standards: BS 1363 and BS 1362 (fuse)

Back Box Depth: 35mm Minimum Cable Size: 3 x 2.5mm² or 2 x 4mm²

Dimensions: 1 Gang (88mm x 88mm x 1.3mm*), 2 Gang (146mm x 88mm x 1.3mm*) *Excluding gasket

Standards: BS EN 60669 Back Box Depth: 25mm Minimum
Cable Size: 1 x 2.5mm² / 2 x 1.5mm² 20A: 1 x 10mm² / 4 x 2.5mm²

Dimensions: 1 Gang (88mm x 88mm x 1.3mm*), 2 Gang (146mm x 88mm x 1.3mm*) *Excluding gasket