

## www.hamilton-litestat.com

## Item Image Wiring **Dimensions** HARTLAND CFX GANG 13A FUSED SPUR DOUBLE POLE ROCKER SWITCH + NEON Hamilton

## 77C SPN BC-B

Hartland CFX Bright Chrome 1 gang 13A Fused Spur Double Pole and Neon. Standard Insert will be Bright Chrome with a Black surround.

Brimany Pango	Hartland CFX	
Primary Range		
Insert Type	Switched Fused Connection Units	
Plate Finish	Bright Chrome	
Frame Finish	<u> </u>	
Switch Colour	Bright Chrome	
Body & Switch Trim	Black	
Height	Single = 86mm	
Width	Single = 86mm	
Depth	Single = 5mm	
Fixing Hole Centres	Box Fixing = 60.3mmBox Fixing = 60.3mm	
Minimum Wall Box Depth	35mm	
Wattage		
Switched Poles	Double	
Current Rating	13 Amp	
Voltage	220/250V AC	
Max load	13 Amp	
Contact Gap Minimum	3mm	
Terminal Capacity 1	3 x 2.5mm2	
Terminal Capacity 2	2 x 4mm2 Multi-Strand	
Terminal Capacity 3	1 x 6mm2	
Terminal Capacity 4		
Terminal Capacity 5		
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-Strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating	-5° to +40°C	
Temperature	-5 to +40 C	
Recommended Location	Indoor use only	
Standard/Approval	BS 1363	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at August 2012 E&OE

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary) Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire Registered in London No. 941624 • VAT Registration No. 222 6607 84







