

# WS7

## 7 litre Vented Water Storage Heaters

The WS7 offers an economical solution to provide stored hot water at point of use and can be mounted undersink using the special monoblock chrome-mixer accessory. These units also benefit from minimal standing heat loss, because they are installed at point of use.

**Application** Hot water storage.

**Key Features** 7 litre capacity, point of use | Choice of 1kW and 3kW models | 300mm swivel spout included | Extended outlets available | Wall bracket and full fixing pack supplied | Adjustable thermostat 15°C - 75°C with frost protection setting.

**Safety Features** Frost protection setting | Integral safety over-temperature thermal fuse | Optional tamper proof cover supplied.

**Capacities** 7 litre.

**Rating** 1kW and 3kW.

**Outer Casing** High quality impact resistant ABS cover.

**Insulation** Polystyrene insulation.

**Water Container** Corrosion resistant polypropylene.

**Heat Unit** Sheathed heating elements.

**Thermostat** Capillary type, externally adjustable - 15°C - 75°C with frost protection setting.


**Pressure** 0.7bar - 10bar (Flow restrictors included).

**Accessories** See opposite page for details.

**Approvals** BEAB Approved | CE.

**Guarantee** 3 year product guarantee (UK).

### Dimensions



### Accessories

**A:** Extended Swivel Spouts 450mm, **B:** 600mm, **C:** Monoblock Vented Chrome Mixer.



### Technical Specification

Cold water 15mm compression | Outlet ½ BSP - swivel spout connection supplied | Restrictors supplied to optimise flow rate | NB: We only recommend the use of the Redring Vented Monoblock Mixer.

### Product Range

Product Reference	Short Code	Cat. No
<b>WS7 3kW</b>	<b>WS73</b>	<b>44780001</b>
<b>WS7 1kW</b>	<b>WS71</b>	<b>44780002</b>
<b>Extended Swivel Spouts 450mm</b>	<b>S1</b>	<b>84780404</b>
<b>Extended Swivel Spouts 600mm</b>	<b>S2</b>	<b>84780405</b>
<b>Mono Vented Chrome Mixer</b>	<b>MCM</b>	<b>84780408</b>