UNICRIMP® NOWAVAILABLE FROMUNICRIMP®

PREVENT CABLES FROM PREMATURE COLLAPSE DURING A FIRE AND KEEP EMERGENCY SERVICES AND THE PUBLIC SAFE.

> Oval mounting slot for varying cable thicknesses

Q-FIRE

Part Number	Description
QC3MBK	METAL CABLE CLEATS 5.0-7.6MM
QC4MBK	METAL CABLE CLEATS 7.7-10.0MM
QC5MBK	METAL CABLE CLEATS 10.1-12.7MM
QC6MBK	METAL CABLE CLEATS 12.6-15.2MM
QC7MBK	METAL CABLE CLEATS 15.1-17.8MM
QC8MBK	METAL CABLE CLEATS 17.7-20.3MM
QC9MBK	METAL CABLE CLEATS 20.2-22.8MM

BS7671 IET Wiring Regulations 18th Edition, Chapter 52: Selection and erection of wiring systems, provides requirements for the methods of support of wiring systems in escape routes.

Part Number	Description
QC10MBK	METAL CABLE CLEATS 22.7-25.4MM
QC11MBK	METAL CABLE CLEATS 25.3-27.7MM
QC12MBK	METAL CABLE CLEATS 27.6-30.5MM
QC14MBK	METAL CABLE CLEATS 30.4-35.5MM
QC16MBK	METAL CABLE CLEATS 35.4-40.6MM
QC18MBK	METAL CABLE CLEATS 40.5-45.7MM
QC20MBK	METAL CABLE CLEATS 45.6-50.8MM

NEW