



**A**

## Key Features

- Accurate, temperature control to within  $\pm 1.5^\circ$  for a comfortable, safe showering experience
- All tactile push button controls with audible adjustment confirmation for ease of operation
- Large LED backlit temperature display
- Phased shutdown safety protection for next user cool start up and scale protection
- Temperature limiter lock option - set at installation
- SmartFit Technology with multi-entry connection options (8 for water and 6 for power) for ease of installation
- Five spray mode easy rub-clean showerhead
- 600mm riser rail with flexible fixing centre brackets
- 1.5 metre flexible shower hose and soap dish with integral shower hose retainer

## Product Range

Item Code:	Model No:	Description	kW
53537101	RGS8T	Glow Thermostatic Electric Shower	8.5
53537201	RGS9T	Glow Thermostatic Electric Shower	9.5

## Dimensions



DEPTH: 75mm



SMARTFIT CONNECTIVITY

## Technical Details

Model	RGS8T	RGS9T
EAN /Bar Code No.	5017084537112	5017084537204
Output (kW)	8.5	9.5
Current Rating (Amps) @240V	35.41	39.58
MCB Rating (Amps)	40	40
Thermostatic Control Accuracy	$\pm 1.5^\circ\text{C}$	$\pm 1.5^\circ\text{C}$
Shower Start-up Temperature	43°C	43°C
Temperature Selection Range	25 - 47°C	25 - 47°C
Thermal Cut-out Protection	49°C	49°C
Energy Rating (Class)	A	A
Energy Rating (%)	39	39
Consumption (kWh/A)	478	478
Load Profile	XS	XS
Sound (dB)	15	15
Operating Pressure psi/(bar)	15 (0.1) – 145 (10)	15 (0.1) – 145 (10)
Minimum Flow Rate (l/min)	1	1
Water Connection	15mm compression or push-fit	
IP Rating	IPX4	IPX4
Box Dimensions (mm)	590 x 250 x 115	590 x 250 x 115
Shower Gross Weight (kg)	3.4	3.4
Shower Net Weight (kg)	2.8	2.8
Pallet Quantity	90	90
Approvals / Mark	BEAB & CE	BEAB & CE
UK Guarantee (years)	3	3

