Mechanical Thermostats

GreenBrook are pleased to introduce the 'KingShield' range of thermostats. In addition to the room thermostats, the range includes two froststats and a cylinder/pipe stat. These mechanical thermostats are easy to install and have an IP rating of IP20. Now available in stylish clam packaging.

Technical Data

Voltage 230V AC resistive load

IP Rating IP20 Class Class II

3 wire operation

Conforms to EN 60730-1/EN 60730-2-7

Part No	Description	Product Information/ Dimensions	
TH90-C	Thermostat Break on Rise	Resistive 10A opening +5° C to +35° C H83 x W83 x D34mm	
TH90C-C	Changeover Contact Thermostat	Resistive 10A opening, 3A closing +5°C to +35°C H83 x W83 x D34mm	C
тн90т-С	Thermostat Tamperproof Break on rise	Resistive 10A opening, 3A closing +5°C to +35°C H83 x W83 x D34mm	
TH90F-C	Froststat For frost protection of building fabric, contents and exposed pipework	Resistive 10A opening -5° C to +15° C H83 x W83 x D34mm	
TH90FT-C	Froststat Tamperproof For frost protection of building fabric, contents & exposed pipework	Resistive 10A opening 3A closing -5°C to +15°C H83 x W83 x D34mm	
TH90CS-C	Cylinder/Pipe Stat Control for boilers and central heating	Resistive 15A opening, 15A closing +20°C to +90°C H120 x W40 x D40mm	

E sales@greenbrook.co.uk W www.greenbrook.co.uk