MIRA JUMP MULTI-FIT

Part Number: 7.5kW White/Chrome 1.1788.477 Part Number: 8.5kW White/Chrome 1.1788.010 Part Number: 9.5kW White/Chrome 1.1788.011 Part Number: 10.8kW White/Chrome 1.1788.012

REPLACES ANY EXISTING ELECTRIC SHOWER

ACCEPTS WATER AND CABLE Entry from the left or the right

TEMPERATURE CONTROL

Pressure stabilised temperature control

EASY TO FIT More space to work under the cover

Integrated pipe channel

Dual terminal blocks

Adjustable slide bar fits over holes left by previous shower kit

EASY TO SERVICE Easy filter access

FOR YOUR CUSTOMER Separate power and temperature/flow controls

Push button on/off

Eco setting saves water and energy

Clearscale[™] reduces limescale by up to 50%

4 spray 9cm showerhead with rub clean nozzles



COLD

TECH DETAILS

TEMPERATURE CONTROL

Control type: Pressure stabilised

INSTALLATION

Power options: 8.5kW 240V AC (7.8kW 230V AC) • 9.5kW 240V AC (8.7kW 230v AC) • 10.8kW 240V AC (9.9kW 230V AC)

Supply voltage: 230v ± 10%

Supply rating: 40 amp (8.5 & 9.5kW); 45 amp (10.8kW)

Terminal Block connections: Maximum 16mm²

Water entry points: Left or right (rising, falling & rear)

Cable entry points: Left or right (rising, falling & rear)

Inlet connections: 15mm plastic stub, compression or push-fit fittings

Outlet connections: ½" BSP Male

SUPPLY CONDITIONS

Minimum maintained pressure: 7.5, 8.5 & 9.5kW: 0.7 bar (7 metre head); 10.8kW 1.0 bar (10 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

PERFORMANCE

Temperature stability: $\pm 6^{\circ}$ C

SAFETY FEATURES

Phased shutdown: No

Factory set to safe max temp: No

Sensi-flo™: No

ACCESSORIES

Wide range of accessories available at www.mirashowers-store.co.uk

TECH DRAWINGS

CE Intertek

