## 13 Amp Switched Socket with USB Charger 2x Outlets 3.1A

Ideal for charging iPad, iPhone, tablets, mobiles, cameras and more 2x Type A USB sockets - 3.1A total output, 5V Twin earth fitted as standard Terminal capacity 3x 2.5mm<sup>2</sup>, 3x 4.0mm<sup>2</sup> & 2x 6.0mm<sup>2</sup> 10 year guarantee







MC522U3

Product	Description	Inner	Outer
Code		Carton	Carton
MC522U3	Double + 2x USB (3.1A)	5	50



## 10 Amp 10AX Plate Switches

• Manufactured to BS EN 60669-1

Product Code

MB512

MB513

MB514

MB543

Code

MC522 MC523

- · Mounting box with 1x 20mm knockouts in each side and rear face
- Terminal capacity 4x 1.0mm², 4x 1.5mm² 2x 2.5mm² & 1x 4.0mm²
- · Backed out captive screws for easy installation



Inner	Outer Carton
 10	50
10	50
10	50
10	50
10	50
5	25

Carton

10

10

Carton

50

25

50

Carton Carton

10

25 50



## 13 Amp Socket Outlets

Description

Single, 2 way

Single, bell push Double, 2 way

Intermediate

Triple, 2 way Quadruple, 2 way

- Manufactured to BS 1363 part 2
- Terminal capacity 3x 2.5mm², 3x 4.0mm² & 2x 6.0mm²
- Single mounting box with 1x 20mm knockouts in each side and rear face
- Colour coded terminals with backed out captive screws for easy installation



MC522



13 Amp RCD Protection

· Maximum load 3120 watts 240V AC

Description

Single DP socket, switched

Double DP socket, switched

Single socket, unswitched

Double socket, unswitched

- Manufactured to BS 7288:2016
- Terminal capacity 3x 2.5mm², 3x 4.0mm² & 2x 6.0mm²
- · Earth terminal in mounting box
- 30 mA trip speed 40ms
- · Mounting box with 1 x 20mm knockouts in each side and rear face

Double, switched socket outlet with RCD

Product Code

MC552RCD

MC554RCD

\*For information on the 2 types of RCD, please see page 12

Description

Fused connection unit



MC522RCD



MC554RCD