

	utlets 3	ed Socket with USB Charger 1A				
		nartphones, tablets, cameras and more				
		x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm² box depth – 25mm				
		standard – Ref. BS 7671:2008				
	ctured to BS			\wedge	 _	
	ared across quarantee	both ports		(A\$A)	_	_
• 10 year	guarantee			APPROVED		
						922U
Round Edge	Square Edge	Description	Inner Carton	Outer Carton		
	922U3	Double SP, switched + 2x USB (3.1A)	5	50		

13 Amp Switched Socket with USB Charger - 3 x Outlets 3.1A

· Ideal for charging smartphones, tablets, cameras and more

- Terminal capacity 3 x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm²
- Minimum mounting box depth 25mm
- Twin earth fitted as standard Ref. BS 7671:2008
- Manufactured to BS1363-2
- · 3.1A shared across both ports
- 10 year guarantee

\wedge	
APPROVED	

USB CHARGER 5.0V TT 3.1A MAX 15.5W	
	822U33

		Carton
822U33 922U33 Double SP, switched + 3x USB (3.1A)	5	50

13 Amp Unswitched Socket with USB Charger - 4 x Outlets 4.2A

- 4 X UI	ullets 4.	2A				
 Terminal Minimum 	capacity 3 : mounting I	nartphones, tablets, cameras and more x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm² pox depth – 25mm tandard – Ref. BS 7671:2008			UBB CHARGER SOV TTZ JA MAX 10.5W	USB CHARGER 5.0 77.2 IA MAX ID3W
		1363-2 tlets shared 2.1A output		ASA		
Round Edge	Square Edge	Description	Inner Carton	Outer Carton		924U44
824U44	924U44	Double, unswitched + 4x USB (4.2A)	5	50		