# **Ceiling Roses**

- · Large capacity earth terminal with locking terminal screw
- · Eight "in-line" terminals all with captive screws
- · Wiring aperture in base with extra knockout for ease of wiring
- Spin-on cover with smooth cable entry for maximum protection of pendant conductor insulation
- Large capacity earth terminal with locking terminal screw
- Base moulded in clear polycarbonate
- · Cover moulded in satin finish urea
- Manufactured to BS67

Product Code	Description	Inner Carton	Outer Carton
561	3.5" diameter	10	100
661	3" diameter	10	100



## Pendant Sets (T2)

- Large capacity earth terminal with locking terminal screw
- Wiring aperture in base with extra knockout for ease of wiring
- 0.75mm pendant flex heat resistant to BS6141
- Spin-on cover with smooth cable entry for maximum protection
- of pendant conductor insulation
- Eight "in-line" terminals all with captive screws
- Manufactured to BS67 and BS EN 60598-2-1

Product Code	Description	Inner Carton	Outer Carton
566	6" flex and 3.5" base	10	100
569	9" flex and 3.5" base	10	100
666	6" flex and 3" base	10	100
666DC	6" pendant set with decorators cover	10	100
669	9" flex and 3" base	10	100
6612	12" flex and 3" base	10	100



### **Batten Holders Enclosed (T2)**

- · Large capacity earth terminal with locking terminal screw
- Diameter of batten lampholder is 80mm (3")
- T2 temperature rated

Ceiling & Lighting | Acc

- · Wiring aperture in base with extra knockout for ease of wiring
- · Wired with heat resistant wire
- · Base cover can be removed without removing HO skirt
- Manufactured to BS EN 61184



Product Code	Description	Inner Carton	Outer Carton
763	2 terminal body, 3 terminals + earth in base, PVC tails, HO skirt	10	100
767	2 terminal body angled, 3 terminals + earth in base and PVC tails, HO skirt	10	100

# **Batten Holders (T2)**

- · Manufactured to BS EN 61184
- · Knock-outs to allow for surface wiring
- 3 Terminals
- For B22 bayonet cap lamps

Product Code	Description	Inner Carton	Outer Carton
752	3 terminals with short skirt	10	100
753	3 terminals with HO skirt	10	100
747	3 terminal angled with HO skirt	10	100
748	3 terminal angled with short skirt	10	100



# Individually bagged Manufactured to BS EN 60669-01

Product Code	Description	Inner Carton	Outer Carton
801	6 Amp 1 way	10	100
802	6 Amp 2 way	10	100
803	45 Amp double pole with power indicator	10	100
804	10 Amp triple pole fan isolator	10	100
801PC	Replacement pull cord, 1.5m	20	200



#### **Decorative Ceiling Roses and Switches**

· Supplied with approximately 1.5 metres of cord

· Supplied with approximately 1.5 metres of cord

Individually bagged

**Ceiling Switches** 

Manufactured to BS EN 60669-01

Product Code	Description	Inner Carton	Outer Carton
802BRG	6 Amp 2 way ceiling switch brass finish	5	50
802CH	6 Amp 2 way ceiling switch chrome finish	5	50
802ST	6 Amp 2 way ceiling switch steel finish	5	50
661BRG	Brass finish cover with polycarbonate 3" diameter base	5	50
661 CH	Chrome finish cover with polycarbonate 3" diameter base	5	50
661ST	Steel finish cover with polycarbonate 3" diameter base	5	50



## Lamp Holders – Heat Resistant (T2)

- · Moulded in robust fully insulating plastic
- Positive cord-grip
   Manufactured to BS EN 61184
- 2A at 250V AC

Description	Inner Carton	Outer Carton
Cord grip with short skirt	20	20
Cord grip with HO skirt	20	20
1/2"/12.6mm 26 BSB threaded entry with short skirt	20	20
10mm threaded entry with short skirt	20	20
Pushbar lamp holder switched $1\!/\!2$ " 26 BSB with threaded entry and short skirt	20	20
Short skirt	100	1000
HO skirt	100	1000
	Cord grip with short skirt Cord grip with HO skirt 1/2"/12.6mm 26 BSB threaded entry with short skirt 10mm threaded entry with short skirt Pushbar lamp holder switched ½" 26 BSB with threaded entry and short skirt Short skirt	Description         Carton           Cord grip with short skirt         20           Cord grip with HO skirt         20           1/2"/12.6mm 26 BSB threaded entry with short skirt         20           10mm threaded entry with short skirt         20           Pushbar lamp holder switched ½" 26 BSB with threaded entry and short skirt         20           Short skirt         100



### Pendant Set - Edison Screw

- · Large capacity earth terminal with locking terminal screw
- Wiring aperture in the base with extra knockout for ease of wiring
- · Base incorporates L, N and loop-in terminals with 8 individual cable entries and captive screws
- Spin-on-cover with smooth cable entry for maximum protection of pendant conductor insulation
- Alternative fixing holes allow for off centre mounting
- 0.75mm² two core circular cable
- · Lamp holder pre-wired to cable ready to be fitted to ceiling rose
- 6"/15cm flex & 3"/80mm diameter base

Product Code	Description	Inner Carton	Outer Carton
666ES14	Pendant set – E14 Edison screw	10	100
666ES27	Pendant set – E27 Edison screw	10	100

