TWO WIRE FIRE REPEATER PANELS MAGDUO





æ





- Compatible with MAGDUO 4 or 8 zones control panels only
- Reports MAGDUO panel events to a remote location
- Capable of performing system controls (i.e. Silence Alarms, Reset, Sound Alarms & Silence Buzzer)
- Maximum of 8 repeater panels can be connected to a single control panel

MAGDUOREP Grey **MAGDUOREPB** Black Conventional Repeater Panel for MAGDUO

Power	
Power	24vDC (Range 21-31vDC)
Consumption	
Quiescent (Back Light Off)	24vDC @ 16mA
Maximum (Back Light and Controls Enabled)	24vDC @ 50mA
Input	
Communication	RS-485
Max. Length Between Panels	500 Meters
Output	
Communication	RS-485
Max. Length Between Panels	500 Meters
Technical spec	
Max. Number per Panel	8
Environment	
Working Temperature	5°C to 50°C
Weight	0.65 Kg
Dimensions	250 x 140 x 85 mm

BPS-1 24V 1 Amp Boxed Power Supply BPS-2 24V 2 Amp Boxed Power Supply

BPS-5 24V 5 Amp Boxed Power Supply

Nb Boxed power supplies require 2 x 12V batteries (not supplied)