



EN54

CE

Made in
EURoHS
COMPLIANT
2002/95/ECCPR
COMPLIANT

MAGDUO4 Grey MAGDUO4B Black 4 Zone Two Wire Fire Panel

- Two Wire fire alarm system
- Active end of line monitoring and head removal
- Up to 32 devices per zone (Dependent on Device Loading Unit: DLU)
- 4 line x 20 character LCD display
- Ability to differentiate between smoke detector, heat detector or a manual call point alarms
- Alarm confirmation feature
- RS485 connection to up to 8 repeater panels
- Event log storing up to 500 events
- 3 enhanced test modes
- Zone can be configured to day/night detection mode
- Delay programming options
- 4 or 8 zone panel can now be configured to accept conventional devices on zones 5 to 8 with the optional conventional zone card
- Certified to EN54 2/4 Standards
- Requires 2 x 12V 3.2Ah batteries (BAT32)
- Optional extended battery box with capacity for 2 x 12V 7.0Ah batteries

Inputs

Max Detectors Per Zone	Up to 32 Devices (Dependant on Device Loading Units , 160 per Zone)
------------------------	---

Power

Mains Supply	230VAC, +10%, -15%, 50/60Hz
Operating Voltage	24vDC (Range 21-31vDC)
Standby Supply	2 x 12V 3.2Ah S.L.A Battery

Outputs

Zone	Up to 4 (300mA)
Monitored Sounder Circuits	Up to 2 (250 mA)
Monitored Relay Circuits	Up to 2 (250 mA)
Auxiliary Output	24vDC (300mA)

Environment

Working Temperature	5°C to 40°C
Dimensions	333 x 333 x 99mm
Weight	2.28 Kg



MAGDUOBBB
Battery Expansion Box for MAGDUO



MAGDUOPK (Pack of 2)
Two Wire Fire Panel Spare Key



MAGDUOPCPS
MAGDUO Software