



Main

Range of product	INS250 INS320...630 INS40...160 INS630b...2500 INSJ400 INV100...250 INV320...630 INV630b...2500 NG160 NG160NA NR100...250 NR400...630 NSC100 NSX100...250 NSX400...630 Easypact CVS100...250 Easypact CVS400...630 INSE80 PowerPact multistandard
Device short name	OF SD SDE SDV
Product or component type	Auxiliary contact
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Early-break Early-make
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	Utilisation category DC-14 : 1 A network: DC at 24 V Utilisation category DC-14 : 0.2 A network: DC at 48 V Utilisation category DC-14 : 0.05 A network: DC at 110 V Utilisation category DC-14 : 0.03 A network: DC at 250 V Utilisation category DC-12 : 6 A network: DC at 24 V Utilisation category DC-12 : 2.5 A network: DC at 48 V Utilisation category DC-12 : 0.6 A network: DC at 110 V Utilisation category DC-12 : 0.3 A network: DC at 250 V Utilisation category AC-15 : 6 A network: AC 50/60 Hz at 48 V Utilisation category AC-15 : 6 A network: AC 50/60 Hz at 24 V Utilisation category AC-15 : 5 A network: AC 50/60 Hz at 110 V Utilisation category AC-15 : 4 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-15 : 2 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-15 : 1.5 A network: AC 50/60 Hz at 480 V Utilisation category AC-15 : 0.1 A network: AC 50/60 Hz at 660/690 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 660/690 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 480 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 48 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 380/440 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 24 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 220/240 V Utilisation category AC-12 : 6 A network: AC 50/60 Hz at 110 V
Minimum load	100 mA at 24 V
Product compatibility	PowerPact H-Frame PowerPact J-Frame PowerPact L-Frame

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.