



DATASHEET



CFR5WW

230V IP65 5W Fire-Rated LED Downlight 3000K

www.mlaccessories.co.uk



MLA PART CODE	CFR5WW
DESCRIPTION	230V IP65 5W Fire-Rated LED Downlight 3000K
NET WEIGHT (KG)	0.18
FINISH	White
DIMENSIONS (MM)	Diameter - 84 Projection - 4 Overall Height - 54 Recessed Depth - 50 Minimum Void - 100
CUT-OUT (MM)	Cut-out Diameter - 55
CONSTRUCTION	Construction - Pressed steel
CLASS	II
IP RATING	IP65 (IP20 from above)
WATTAGE (W)	5
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	570
LUMENS LIGHT SOURCE ONLY (LM)	740
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	149.6
CIRCUIT WATTAGE (W)	5.01
CCT	3000K
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.030
DISPLACEMENT FACTOR	>0.7
SVM	0.03
PST-LM	0.135
BEAM ANGLE (DEGREES)	60

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	Yes*
FIRE-RATED	Tested to 30/60/90 minutes
I-JOIST RATED	30 minutes
WEB-JOIST RATED	30 minutes
IC RATED	No
ACOUSTIC RATED	Yes
OPERATING TEMPERATURE	-25~45°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
DRIVER	EFFICIENCY FULL LOAD - 84
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270802931

Date Created: 18/07/2023 09:59

