

Plugs and connectors – Wall mounted inlets

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request. For drawings and dimensions see page 105 - 117.



Wall mounted inlet

for internal and external fixing, for hinged lids for retrofit see part no. 41482 and 41489

IP 44
Std. Pack. Qty: 10
Drawing: 2 MB 213

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz	>50 - 500 V 300-500 Hz
16	3	843	844				



Wall mounted inlet

with hinged lid, for internal and external fixing

IP 44
Std. Pack. Qty: 10
Drawing: 2 MB 212

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz	>50 - 500 V 300-500 Hz
16	3	846	847				



Wall mounted inlet

for external fixing, for hinged lids for retrofit see part no. 41482 and 41489

IP 44
Std. Pack. Qty: 10
Drawing: 2 MB 221

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz	>50 - 500 V 300-500 Hz
16	4			800			
16	5			801			
32	3		802				
32	4			803			
32	5			804			



Wall mounted inlet

enclosure base with stamped recess for quick cutting out

IP 44
Std. Pack. Qty: 10
Drawing: 2 MB 32

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz	>50 - 500 V 300-500 Hz
16	3	331	332	333			
16	4	334	335	336	337	921	922
16	5	340	341	342	2359	2668	2400
32	3	343	344	345			
32	4	346	347	348	349		
32	5	352	353	354	2386		



Wall mounted inlet

for a suitable watertight protective cover for 63 A see part no. 40434

IP 67
Std. Pack. Qty: 5/3
Drawing: 2 MB 36

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz	>50 - 500 V 300-500 Hz
63	3	1216	1107	1217			
63	4	355	356	357	358		
63	5	359	360	361			
125	4	362	363	364	365		
125	5	366	367	368			



Hinged lid for retrofitting for wall mounted inlets

Std. Pack. Qty: 10

Description	Part no.
for part no. 843 and 844	41482
for part no. 800, 801 and 3517	41489