

# "DAVE SAYS" OUALITY MAKES THE DIFFERENCE

Screwdriver type testers contain an indicator in the handle which lights up when the point is touched on voltages between 220-250V and a finger or thumb is placed on the end of the tester to create a circuit.

Non-contact voltage detectors work by sensing the fluctuations in the electric field which surround AC charged objects. This means no contact with the circuit is ever needed giving the user extra safety.







#### **EURO MAINS TESTERS**

Manufactured to the latest UK and European specifications with integral pocket clip and Neon indicator showing current present between 120 - 250V/AC. Display packed.

Stock No.	Part No.	Length
	EMT1D EMT2D	150mm 190mm





Multi-functional tester with plain slot blade for checking wiring without dismantling or having any contact with live parts. Manufactured to the latest UK and European specifications with integral pocket clip and Neon indicator showing current present between 70 - 250V/AC. Display packed.

Stock No.			
64517			



### **MAINS TESTERS**

Manufactured to the latest UK and European specifications with integral pocket clip and Neon indicator showing current present between 120 - 250V. Display packed.

Stock No.	Length
64506	140mm
64510	190mm





For telephone and computer network installation and maintenance. Terminates wire and cuts off excess. Suitable for all CW1308 telecom cable. Cable locking, insertion blades and cable shears included. Display packed.

Stock No. 40417





# CAT III 1000V NON CONTACT VOLTAGE TESTER

**Expert Quality**, non contact voltage tester with integrated inspection lamp. Suitable for identifying live wires, broken wires and fault finding. Sensitive voltage detection between the range of 100-600V. Fitted with inspection light on one end and audible/visual indicators. Powered by 2 x AAA batteries (supplied).

Stock No.			
34278			



# CAT III 600V NON CONTACT VOLTAGE TESTER

Non contact voltage tester. Suitable for identifying live wires, broken wires and fault finding. Voltage detection between the range of 200-600V. Powered by 2 x AAA batteries (sold separately). Display packed.

Stock No. 34277

