




Architectural downlights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled


GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Easy to install compared to halogen
Runs cool - no need for a fan

Ø35mm



FIBRE LED LIGHT

Fibre optic LED light injector

FEATURES

Wattage	1W
IP rating	IP20
Colour flexibility	Fixed colour
Tilttable	No
Input	350mA
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Install connector type	Flying lead
Cut out size	N/A
Bathroom zone	1
Construction material	Aluminium
Weight	40g
Maximum ambient temperature	35°C
Electric class [1, 2, 3]	3

PHOTOMETRICS @ 25°C

Product code	Finish	Colour	CRI	lm
FIBRE LED LIGHT NW	Matt silver anodised	4000K	>80Ra	-

WIRING INFORMATION

Cable / flying lead	1m (0.205mm² red & black PTFE)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	-	Yes	No	2	1	9
PLR/350 1-5	-	Yes	No	1	1	5
PLD UNI-DRIVE 350mA	-	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

FIBRE LED 1/30	Fibre optic strands	Sold separately	127
FIBRE LED 2/30	Fibre optic strands	Sold separately	127
UY2 CONNECTOR	Quick waterproof connector	Sold separately	422
DM298GRID	LED mains grid dimmer	Sold separately	107