
Decorative wall lights.

01604 495 151 collingwoodlighting.com








GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Plug & play connector for quick installation Thread and nut for secure fitting Small & discreet

Beam angle: 110° 180° 150° 600 cd / klm 120° 400 90° 60° 30° 0°





LED LYTE IP T

IP rated threaded mini LED light

FEATURES

Wattage	1W
IP rating	IP65
Colour flexibility	Fixed colour
Tiltable	No
Rotatable	No
Dimmable	No
Input	350mA
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Cut out size	Ø 26mm
Bathroom zone	1
Inrush current	N/A
Construction material	Anodised aluminium
Weight	44g
Maximum ambient temperature	35°C
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
LED LYTE IP T NW	4000K	110°	>70Ra	82	82	46
LED LYTE IP T 27	2700K	110°	>80Ra	58	58	29
LED LYTE IP T BL	Blue	110°	-	-	-	-

WIRING INFORMATION

Cable / flying lead	1m (0.205mm² red & black PTFE)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/PP/350 1-9 (Plug & play)	-	Yes	No	1	1	9
PLR/350 1-5	-	Yes	No	1	1	5
PLD UNI-DRIVE 350mA	-	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

LED LYTE 1M EXT	1m plug & play extension lead	Sold separately	154
LED LYTE 6 WAY EXT	6-way 1m plug & play extension lead	Sold separately	154
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold separately	422