

Driver comparison.

For full driver specifications visit our website collingwoodlighting.com

	RATED WATTAGE (OUTPUT)	OUTPUT VOLTAGE	OUTPUT CURRENT	INPUT WATTAGE (MAX)	INPUT VOLTAGE	INPUT CURRENT (MAX)	INRUSH CURRENT	POWER FACTOR	AMBIENT TEMP. (TA = °C)	CONTROL	DOUBLE INSULATION	EFFICIENCY	IP RATING	PLUG & PLAY
 PSMD35039	10W	8-28V	350mA	13W	220-240V AC	0.06A	33A 0.15ms	>0.9	40 °C	Mains dimmable	Yes	75% min.	IP20	
 PSMD3501324	24W	34-68.5V	350mA	30W	220-240V AC	0.12A	20A 0.13ms	0.95	45 °C	Mains dimmable	Yes	80% min.	IP20	
 PSDAL350M	N/A (see page 406-411)	2-74V	350mA	30W	110-240V AC	0.25A	20A 0.4ms	>0.95	-25 °C to 50 °C	Push, 1-10V & DALI dimmable	Yes	90%	IP20	
 PSDIM350	N/A (see page 406-411)	2 - 74V	350mA	30W	110-240V AC	0.25A	20A 0.4ms	>0.95	-25 °C to 50 °C	Push & 1-10V dimmable	Yes	>80%	IP20	
 PLD UNI-DRIVE 350MA	N/A (see page 406-411)	2-46V	350mA	18W	110-240V AC	0.14A	5A 0.05ms	0.98	-25 °C to 50 °C	Push & 1-10V dimmable	Yes	80%	IP20	
 PSDIN350	N/A (see page 406-411)	2-46V	350mA	30W	220-240V AC	0.16A	5A 0.05ms	0.95	-25 °C to 50 °C	1-10V dimmable	Yes	88%	IP20	
 PLDCC/350/10-28	N/A (see page 406-411)	2-22V	350mA		10-28V DC				40 °C	Non-dimmable		60%	IP20	
 PLR/350 1-5	N/A (see page 406-411)	3-23V	350mA	14W	220-240V AC	0.07A	12.8A 0.6ms	0.6	40 °C	Non-dimmable	Yes	>70%	IP40	
 PLU/350 1-9	N/A (see page 406-411)	2.8-27V	350mA	25W	220-240V AC	0.14A	25.5A 0.6ms	0.55	40 °C	Non-dimmable	Yes	80%	IP40	
 PSIP3509W	N/A (see page 406-411)	2.5-25v	350mA	11W	220-240V AC	0.05A	8A 0.1ms	>0.9	50 °C	Non-dimmable	Yes	82% with full load	IP65	
 PSIP35018W	N/A (see page 406-411)	25-50v	350mA	20W	220-240V AC	0.1A	13A 0.1ms	>0.9	50 °C	Non-dimmable	Yes	83% with full load	IP65	
 PLU/PP/350 1-9	N/A (see page 406-411)	2.8-27V	350mA	25W	220-240V AC	0.14A	25.5A 0.6ms	0.55	40 °C	Non-dimmable	Yes	80%	IP40	Yes
 PLU/PP6/350 1-9	N/A (see page 406-411)	2.8-27V	350mA	25W	220-240V AC	0.14A	25.5A 0.6ms	0.55	40 °C	Non-dimmable	Yes	80%	IP40	Yes

LOOP IN / LOOP OUT	DIN RAIL MOUNT	PROTECTION	SELV	DIMENSIONS (MM)	WEIGHT	CONNECTION OUTPUT	INPUT CABLE (M)	OUTPUT CABLE	ACCESSORIES	WARRANTY
		Short circuit, overload & over current	Yes	H: 19.2mm L: 123mm W: 44.6mm		Terminals	0.5-1.5mm ²	0.5-1.5mm ²		3 year guarantee
		Short circuit, overload & over current	Yes	H: 22mm L: 155mm W: 35mm		Terminals	0.5-1.5mm ²	0.5-1.5mm ²		3 year guarantee
		Short circuit, overload & overheating	Yes	H: 22mm L: 123mm W: 79mm		Terminals	0.5-1.5mm ² max.	0.5-1.5mm ² max.	4m sync cable SYNC CABLE 4M	5 year guarantee
		Short circuit, overload & overheating	Yes	H: 22mm L: 123mm W: 79mm		Terminals	0.5-2.5mm ² max.	0.5-2.5mm ² max.	Grid dimmer kit PDC/GRID DIMMER 4m sync cable SYNC CABLE 4M	5 year guarantee
		Short circuit, overload & overheating	Yes	H: 22mm L: 103mm W: 67mm		Terminals	0.5-1.5mm ² max.	0.5-1.5mm ² max.	Grid dimmer kit PDC/GRID DIMMER 4m sync cable SYNC CABLE 4M	5 year guarantee
	Yes	Short circuit, overload & overheating	Yes	H: 36mm L: 70mm W: 90mm		Terminals	0.5-4mm ² max.	0.5-2.5mm ² max.	Grid dimmer kit PDC/GRID DIMMER 4m sync cable SYNC CABLE 4M	5 year guarantee
			Yes	H: 12mm L: 40mm W: 18mm		Flying leads	0.2	0.2		1 year guarantee
		Short circuit, overload & overheating	Yes	H: 19mm Ø: 53mm		Flying leads	0.2	0.2		1 year guarantee
Yes		Short circuit, overload & overheating	Yes	H: 28mm L: 111mm W: 48mm		Loop-in loop-out terminals	1.5mm ² max.	1.5mm ² max.	PLU weatherproof housing IX 265	1 year guarantee
		Short circuit, overload & overheating	Yes	H: 24mm L: 160mm W: 38mm		Flying leads	0.2	0.2		5 year guarantee
		Short circuit, overload & overheating	Yes	H: 25mm L: 42mm W: 180mm		Flying leads	0.2	0.2		5 year guarantee
Yes		Short circuit, overload & overheating	Yes	H: 28mm L: 111mm W: 48mm		Loop-in loop-out terminals	1.5mm ² max.	1.5mm ² max.	1m Plug & Play extension lead LED LYTE 1M EXT 6-way Plug & Play extension lead LED LYTE 6 WAY EXT	1 year guarantee
Yes		Short circuit, overload & overheating	Yes	H: 28mm L: 111mm W: 48mm		Loop-in loop-out terminals	0.5-1.5mm ² max.	0.5-1.5mm ² max.	1m Plug & Play extension lead LED LYTE 1M EXT 6-way Plug & Play extension lead LED LYTE 6 WAY EXT	1 year guarantee