




## Residential downlights.

01604 495 151  
collingwoodlighting.com

 @collingwoodLED

 /collingwoodlighting

 collingwoodled

### GUARANTEE / WARRANTY

3 year guarantee on LED driver,  
1 year guarantee on battery

### FEATURES & BENEFITS

Provides minimum of 3 hours of emergency lighting

Green light indicates charging of batteries

Pre-wired service offers peace of mind and reduces installation time

# LEDEP06

Emergency pack for maintained lighting assembly - 3hr minimum

### FEATURES

Wattage	3W
IP rating	IP20

### INSTALLATION INFORMATION

Double Insulation	Yes
Inrush current	20A 0.012ms
Construction material	Plastic
Weight	420g
Case temperature (tc = °C)	70
Maximum ambient temperature	55°C
SELV	Yes
Electric class (1, 2, 3)	2

### PRODUCT CODE

Product code	Description
LEDEP06	Emergency pack for maintained lighting assembly - 3hr minimum

### WIRING INFORMATION

Cable / flying lead	300mm 2-core 0.75mm <sup>2</sup>
Type of wiring required	Parallel

### USE WITH

H2 Pro 550 SPS	Single point source, dimmable, fire-rated LED downlight
H2 Pro 550 CS*	Colour switchable, dimmable, fire-rated LED downlight
H2 Pro 700	Dimmable, fire-rated LED downlight
H2 Pro Dusk	Dim to warm, fire-rated LED downlight
H2 Pro Elect	Low glare, dimmable, fire-rated LED downlight
H2 Pro Elect Trimless	Low glare, plaster-in, trimless, dimmable, fire-rated LED downlight
H4 Pro 550 SPS	Adjustable, single point source, dimmable, fire-rated LED downlight
H4 Pro 700	Adjustable, dimmable fire-rated LED downlight
H4 Pro Elect	Adjustable, low glare, dimmable, fire-rated LED downlight
H5 500 Symmetric	Low glare, fire-rated LED downlight
H5 500 Asymmetric	Low glare, fire-rated LED downlight

\*3000K when operating in emergency mode

