

Residential floodlights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled



GUARANTEE / WARRANTY

3 year extended warranty

FEATURES & BENEFITS

Colour switchable
IP65
118lm/W
180° tilt
360° rotation - complete adjustability
Supplied with 1m cable
25,000 hours L70 / B50
Flicker free
Wide 120° beam angle, reducing the number of fittings per area required

Beam angle: C0/C180 C90/C270



FL10

100W colour switchable floodlight

FEATURES

Wattage	100W
IP rating	IP65
IK rating	IK07
Colour flexibility	Colour switchable
Tilttable	180°
Rotatable	360°
UGR	UGR 14
Dimmable	No
Input	Mains AC
LED lifetime	25,000h
SDCM	4SDCM

INSTALLATION INFORMATION

Inrush current	75A 0.005ms
Construction material	Black painted cast aluminium
Weight	2100g
Maximum ambient temperature	40°C
Electric class (1, 2, 3)	1

PHOTOMETRICS @ 25°C

Product code	Finish	Sensor	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
FL10BXCS	Black	Non PIR sensor	6500K	120°	>80Ra	10970	110	4575
			4000K	120°	>80Ra	11810	118	4926
			3000K	120°	>80Ra	10250	103	4275

WIRING INFORMATION

Cable / flying lead	1m H05RN-F rubberised cable 3x1.0mm² Ø7mm
Type of wiring required	Parallel

ACCESSORIES

N/A	No accessories required
-----	-------------------------