

90%

ENERGY SAVINGS

LED TO HALOGEN EQUIVALENT

	HALOGEN Wattage
8w	100w
15w	200w
22w	300w
38w	500w

**LED = REDUCED
POWER CONSUMPTION**



30,000
Hours Life

3000K
Warm White

OR

5000K
Neutral White

Features & Benefits

- Market leading LED floodlight; ideal for multi-purpose residential use
- Die-cast aluminium housing for maximum durability
- Easy installation with a fit and tilt bracket
- Various colour temperatures available to suit all applications
- Supplied with 1m of cable; ideal where through-wall wiring is necessary

Fit & Tilt Installation made simple



PIR Detection with override functionality


This unique feature allows the PIR sensor to operate in Dusk till Dawn mode. However it will only activate depending on ambient light level set on the PIR.

To initiate Override Facility turn the power supply OFF/ON/OFF/ON within 2 seconds.

To turn Override Facility OFF, turn the power off for a minimum of 5 seconds, this will reset back to full automatic PIR detection of the installation.

10m

120°
**PIR DETECTION
RANGE**



View from below

Slimline Guardian Floodlights



Standard

*Replace 'B' with 'W' for White option (not available in 38W)

CAT NO.	LUMENS	WATTAGE	COLOUR TEMP	IP RATING	PACK QTY
LFS6B130	600	8W	3000K	IP65	5
LFS6B150	600	8W	5000K	IP65	5
LFS12B130	1200	15W	3000K	IP65	5
LFS12B150	1200	15W	5000K	IP65	5
LFS18B130	1800	22W	3000K	IP65	5
LFS18B150	1800	22W	5000K	IP65	5
LFS30B130	3000	38W	3000K	IP65	4
LFS30B150	3000	38W	5000K	IP65	4

PIR

*Replace 'B' with 'W' for White option (not available in 38W)

CAT NO.	LUMENS	WATTAGE	COLOUR TEMP	IP RATING	PACK QTY
LFSP6B130	600	8W	3000K	IP44	5
LFSP6B150	600	8W	5000K	IP44	5
LFSP12B130	1200	15W	3000K	IP44	5
LFSP12B150	1200	15W	5000K	IP44	5
LFSP18B130	1800	22W	3000K	IP44	5
LFSP18B150	1800	22W	5000K	IP44	5
LFSP30B130	3000	38W	3000K	IP44	4
LFSP30B150	3000	38W	5000K	IP44	4

