


BS EN 61386 Class 4 Conduit

- Hot dipped galvanised inside and out to Class 4
- Ink Jet marked
- Threaded at both ends
- Each length supplied with one coupler and one plastic thread protector cap
- Available in 20mm and 25mm diameter and 3.00m and 3.75m lengths
- In compliance with BS EN 61386



DT20300

Catalogue Code	Product Diameter	Length	Lengths per master bundle	Metres per master bundle	Lengths per small bundle
DT20300	20mm	3.00m	400	1200m	8
DT20375		3.75m		1500m	
DT25300	25mm	3.00m	320	960m	
DT25375		3.75m		1200m	

BS 4568 and BS EN 61386 Class 4 Conduit

- Hot dipped galvanised inside and out to Class 4
- Hard stamped during manufacturing process
- Threaded at both ends
- Each length supplied with one coupler and one plastic thread protector cap
- Available in 20mm, 25mm and 32mm diameter in 3.75m lengths
- In compliance with BS 4568 and BS EN 61386



DTS25375*

Catalogue Code	Product Diameter	Length	Lengths per master bundle	Metres per master bundle	Lengths per small bundle
DTS20375*	20mm	3.75m	400	1500m	8
DTS25375*	25mm		320	1200m	
DTS32375	32mm		100	375m	4

*Special order product, minimum order quantity and lead time applies