

NVC UK - NVC Lighting Limited  
NVC Park 201, Hollymoor Way, Rubery,  
Birmingham, B31 5HE  
T +44 (0)121 457 6340  
E sales@nvcuk.com

NVC NORDICS - NVC Lighting AB  
Albybergsringen 3b 137 69 Österhaninge  
T +46(0)8 735 55 40  
Sweden info@nvc-lighting.se  
Finland info@nvcclighting.fi  
Denmark info@nvcclighting.dk



## DATASHEET

### PORTLAND

Portland 15W LED IP54 White Opal M3 Lithium 840-850

IP54 CCT Selectable Decorative LED Bulkhead  
Polycarbonate Base, Bezel & Micro-Prismatic Controller  
For Commercial Indoor Areas



| GENERAL INFORMATION                            |                                |
|------------------------------------------------|--------------------------------|
| Product Code                                   | NPO15/WH/M3/840-850            |
| Product Range                                  | Amenity                        |
| Product Category                               | Amenity                        |
| IP Rating                                      | 54                             |
| IK Rating                                      | N/A                            |
| Warranty                                       | 7 Years                        |
| DIMENSION/WEIGHT                               |                                |
| Dimensions Circular (DIA x H) (mm)             | DIA=Ø325, H=100                |
| Dimensions Square/Rectangular (L x W x H) (mm) | L=0, W=0, H=0                  |
| Cut-out Size (mm)                              | 0                              |
| Product Weight (Kg)                            | 1.9                            |
| CONSTRUCTION                                   |                                |
| Body Material                                  | PC                             |
| Body Colour                                    | White                          |
| Optical Material                               | N/A                            |
| Optical Finish                                 | N/A                            |
| Termination                                    | 5x2x2.5mm sq. Push In Terminal |
| Driver - Integral or Remote                    | Integral                       |
| PACKAGING                                      |                                |
| Carton Dimensions (mm)                         | N/A                            |
| Quantity per Outer Carton                      | N/A                            |
| Total Weight inc. Carton (Kg)                  | N/A                            |

| LUMINAIRE PERFORMANCE        |               |
|------------------------------|---------------|
| Energy Rating                | E             |
| Luminaire Lumens (lm)        | 1320          |
| Power Consumption (W)        | 16.7          |
| LED Lumens (lm/W)            | 155           |
| Efficacy (l.lm/c.W)          | 104           |
| Operating Temp. (Min/Max)    | 0°C to 25°C   |
| LIGHT SOURCE                 |               |
| Type                         | LED           |
| Correlated Colour Temp.      | 4000 / 5000   |
| Colour Rendering Index (CRI) | >80           |
| Lumen Depreciation           | L80 100000    |
| SDCM                         | <3            |
| ELECTRICAL INPUT             |               |
| VOLTAGE (V)                  | 220-240V AC   |
| Operating Frequency          | 50            |
| In Rush                      | <25A          |
| Drivers per MCB*             | B10=16 B16=28 |
| Class                        | Class 1       |
| Power Factor                 | >0.95         |
| Cable Entry                  | Back          |
| ELECTRICAL OUTPUT            |               |
| Forward Current (mA)         | -             |
| Forward Voltage (Vf)         | N/A           |
| EMERGENCY DATA               |               |
| Mode of Operation            | Maintained    |
| Battery Duration             | 3 Hours       |
| Battery Type                 | LiFePO4       |
| Battery Specification        | 6.4V 1.0Ah    |
| Ballast Lumen Factor (BLF)   | 6.8           |
| DIMMING                      |               |
| DALI                         | N/A           |
| OTHER                        | N/A           |
| Switch Dim                   | N/A           |
| Corridor Function            | N/A           |
| SENSORS                      |               |
| Microwave                    | N/A           |
| PIR                          | N/A           |
| STANDARDS/APPROVALS          |               |
| CE Marked                    | Yes           |
| Certificate of Conformity    | Yes           |
| Accreditations               | N/A           |
| BARCODE                      |               |
| EAN NUMBER                   | 5055943086388 |

\* GUIDE ONLY

