

GU10 PAR16 4W (52W) 4000K 390lm Non-Dimmable Lamp*Partcode: ILGU10NE103 / Page: 1*

The Integral LED Classic GU10 range offers a fantastic ratio of value and performance. By incorporating a stylish engineered lens in an affordable GU10, the Classic offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED.

Product Details

Partcode: ILGU10NE103

Check Code: 522628

Range Name: Classic

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: GU10

Warranty: 2 Years

CE / RoHS: Yes

Physical Data

Base Type: GU10

Base Colour: Matt white

Product Finish: Matt white

Spot Type: SMD with "COB like effect"

Optic: Designed to give a Classic Look

Material: Plastic and Aluminium heat-sink, Injection moulded diffuser

Construction: Plastic White and "Classic look" difuser lens

Physical Data

Length: 54mm

Width: 50mm

Weight (Unpackaged Single Unit): 25g

Lamp or Luminaire Shape: Round

Lamp Fixing: Downlight

Electrical Data

Voltage Range: 220-240V

Power Consumption: 4.0 Watts

Driver included: Yes

Electric Current: AC

Ampage: 34.00mA

Frequency Range: 50/60 Hz

Power Factor: ≥ 0.40

Wattage Equivalent: 52 Watts

Dimming: Non-dimmable

LVD Certified: Yes

EN: EN-62560

Light Data

Useful Lumens: 360lm (Rated luminous flux in a 90° cone)

Lumens: 390lm

Lumens per Watt: 98.0lm/W

Peak Intensity: 750Cd

Beam Angle: 36°

Correlated Colour Temperature (CCT): 4000k

Colour Temperature: Cool White

Colour Rendering Index (CRI): ≥ 80

LED Type: Surface mounted device (SMD)


Instant on - Less than 1 second: Yes

Lifetime: 15,000 hrs

Switching Cycles: $>7,500$ X

Partcode: ILGU10NE103 / Page: 3

Environmental



Energy Rating: A++

Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 40 degrees

Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788241003

Packaged Weight (Unit of 1): 50g

Length (unit of 1): 55mm

Width (unit of 1): 55mm

Depth (unit of 1): 60mm

Outer packaging info available on website

Product data last updated on: Monday, April 8, 2019 - 10:20