

Description

KSR Integral Mounted
Microwave Sensor.



General

Colour Options	White Only
Sensor Type	Microwave - MW
Product Warranty	5 Years from Date of Purchase
Mounting Method	Screw Mount, Integral to Luminaires
EAN	506049951****

Electrical Parameters

Supply Voltage	220-240V AC
Frequency	50/60Hz
Parasitic Power	<0.5W
Max LED Switching (W)	300W
Max Halogen Switching (W)	1200W
Max Fluorescent Switching (W)	300W

Detection Parameters

Max Detection Range	Wall Mounted – 5-15m, Ceiling Mounted 1-8m
Detection Range Setting	20%, 50%, 75% & 100%
Detection Angle	360°
Time Settings	5s, 30s, 1min, 5min, 10min, 20min & 30min
Lux Settings	2 lux, 5 lux, 20 lux, 50 lux, 2000 lux
Detection Speed	0.6 – 1.5 M/Sec
Tilt Angle	N/A Fixed Position Sensor
Rotation Range	N/A Fixed Position Sensor
Mounting Height	Wall – 1.5 to 3.5m, Ceiling – 2-6m

Classifications and Approvals

Earth Class	Class II, No Earth Required
IP Rating	IP20
CE Marked	Yes
Designed In Accordance to	BSEN

