

# OUTDOOR WALL PACK COMPACT LIGHT SENSOR IP65 3150LM 30W 4000K 115 BEAM BLACK INTEGRAL

ILWPA001



Integral Compact Tough Wall Pack Lights are ideal for perimeter lighting as well as pedestrian and vehicle access areas in commercial and industrial environments. The IP65 weatherproof and IK08 impact-resistant cast aluminium body makes it perfectly suitable for outdoor installation. This model features a light sensor, so the unit automatically switches on at dusk and off at dawn, increasing efficiency.

#### **Details**

Quick Order Code: 926174

**Barcode**: 5055788241782

Category:LuminairesRange Name:Compact ToughProduct Type:Wall PacksProduct Body Finish:Dark BrownMarket Segment:OutdoorFinish:Dark Brown

Features: Dusk-to-Dawn Sensor

Warranty (Years): 3
CE RoHS: Yes

#### **Physical Data**

Product Length (mm): 241.7
Product Depth (mm): 76
Product Width (mm): 150
Product Weight (g): 1170

Optic: Polycarbonate diffuser
Material: ADC12 Aluminium

**Construction:** Aluminium heat-sink, PC injection moulded driver case

Bulb or Luminaire Shape: Rectangle Luminaire Fixing: Wall

Mounting Type: Rear Cable Entry

Placement / Application: Outdoor

#### **Electrical Data**

Power Consumption (w): 30

Power Factor: 0.95 Input Voltage (V): 220-240

**Dimming:** Non-Dimmable

Electric Current: AC

**EN:** EN-60598

LVD Certified: Yes

### **Light Data**

Luminous Flux in Lumens (Im): 3150
Luminous efficacy (Im/W): 105
Correlated Colour Temperature (CCT) (K): 4000


Colour Temperature Name: Cool White

Beam Angle:115Colour Rendering Index (CRI):80Lifetime (hours):50000Switching Cycles:100000Useful Lumens (Im):3150

#### **Environment**

**EN:** EN-60598

LVD Certified: Yes **CE RoHS:** Yes **EU Luminaire:** L Hg 0% (Mercury Free): Yes **IK Rating (Impact Protection): IK08 IP Rating (Ingress Protection):** IP65 **Lowest Operating Temperature (°C):** 0 **Maximum Operating Temperature (°C):** 45



## **Packaging**

Package Weight (g): 1370
Package Length (mm): 255

Package Width (mm): Portal.inte@al-led.com

Package Depth (mm): 100

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE