

GX53 BULB 545LM 5W 4000K NON-DIMM 100 BEAM FROSTED INTEGRAL

ILGX53N002



Integral LED GX53 lamps are an ideal retrofit lamp for GX53 fittings in kitchen units, display cabinets and under-shelf lighting. These highly efficient lamps offer significant energy savings and long life compared to halogen equivalents.

Details

Quick Order Code: 378588

Barcode: 5055788222941

Category:LampsRange Name:GX53Product Type:GX53

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

Physical Data

Product Length (mm): 75
Product Width (mm): 25
Product Weight (g): 65

Material: Aluminium, Polycarbonate

Base Term: GX53 Bulb Base: GX53

Construction: SMD, Plastic Body

Globe Finish: Frosted Globe Type: GX53

Bulb Fixing: Under Shelf Lighting, Display Cabinets

Bulb or Luminaire Shape: Round

Placement / Application: Indoor, Outdoor, General Lighting

Electrical Data

| Power (W): | 5 |
|-------------------------|------|
| Power Consumption (w): | 5 |
| Power Factor: | 0.53 |
| Wattage equivalent (W): | 40 |
| Amperage (mA): | 42 |

Dimming: Non-Dimmable

Driver Included: Yes
Electric Current: AC

EN: EN-62560

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 545
Luminous efficacy (Im/W): 109
Correlated Colour Temperature (CCT) (K): 4000
Colour Temperature Name: White
Beam Angle: 110
Colour Rendering Index (CRI): 80
Instant on (Less than 1 second): Yes


LED Type: Filament chip

Lifetime (hours): 15000 Switching Cycles: 7500

Environment

EN: EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Energy Rating:** A+ F **New Energy Rating:** Hg 0% (Mercury Free): Yes IP20 **IP Rating (Ingress Protection): Lowest Operating Temperature (°C):** -15 **Maximum Operating Temperature (°C):** 45



Packaging

Package Weight (g): 65
Package Length (mm): 75

Package Width (mm): Portal.integral-led.com

Package Depth (mm): 26

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE