

**VALUE+ PANEL 600X600 3800LM 38W 4000K NON-DIMM 100LM/W EDGELIT INTEGRAL**

ILP6060E002



This is a 38W, 3800lm 600x600 Integral LED Value+ panel. It delivers a uniform white light across the whole of its surface. The high level of efficacy (100lm/W) offers savings in running cost against traditional 72W fluorescent fittings as well as many other LED panels. The panels are an ideal solution for many business applications.

**Details**

<b>Quick Order Code:</b>	431817
<b>Barcode:</b>	5055788225515
<b>Category:</b>	Panels
<b>Range Name:</b>	Value+
<b>Product Type:</b>	600 x 600
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Commercial indoor
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	596
<b>Product Depth (mm):</b>	8.2
<b>Product Width (mm):</b>	596
<b>Product Weight (g):</b>	2800
<b>Optic:</b>	Opal diffuser
<b>Material:</b>	Aluminium, Steel, PS Diffuser
<b>Construction:</b>	extruded Aluminium, steel back, LGP sheet and PS diffuser
<b>Luminaire Fixing:</b>	Recessed in ceiling grid, surface mounted or suspended (additional surface mounted or suspension kit required)
<b>Panel Equivalent:</b>	The Luminaire is Class II
<b>Placement / Application:</b>	Indoor, General Lighting

**Electrical Data**

<b>Power (W):</b>	38
-------------------	----

<b>Power Consumption (w):</b>	38
<b>Power Factor:</b>	0.9
<b>Wattage equivalent (W):</b>	86.4
<b>Amperage (mA):</b>	835
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	3800, 3600
<b>Luminous efficacy (lm/W):</b>	100
<b>Peak Intensity (Cd):</b>	1004
<b>Correlated Colour Temperature (CCT) (K):</b>	4000
<b>Colour Temperature:</b>	4000K - Cool White
<b>Colour Temperature Name:</b>	Cool White
<b>Beam Angle:</b>	110
<b>Colour Rendering Index (CRI):</b>	80
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Size (mm):</b>	2835
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	30000
<b>Lighting Method:</b>	Edge-lit
<b>Switching Cycles:</b>	25000

## Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Back/Recessed side):</b>	IP20
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-10
<b>Maximum Operating Temperature (°C):</b>	40
<b>TP rating:</b>	None

## Packaging

<b>Package Weight (g):</b>	3300
<b>Package Length (mm):</b>	686
<b>Package Width (mm):</b>	640
<b>Package Depth (mm):</b>	40
<b>Qty per euro pallet:</b>	75