OUTDOOR DECORATIVE WALL LIGHT PABLO IP54 300LM 8W 3000K UP/DOWN LIGHT DARK GREY INTEGRAL

ILDEA010



Discover Integral's new outdoor range. Light up the exterior of your home with these compact, stylish and contemporary LED luminaires. Weatherproof and hard-wearing, this range is designed to last against the elements while bringing a designer look to your surroundings. Named after one of the great forefathers of Cubism, the Pablo rectangular wall light creates a striking up/down effect. The sleek design brings a contemporary feel to any area.

Details

| Quick Order Code: | 326761 |
|--------------------------|---|
| Barcode: | 5055788232506 |
| Category: | Luminaires |
| Range Name: | Wall Light |
| Product Type: | Outdoor |
| Market Segment: | Residential Outdoor |
| Warranty (Years): | 3 |
| CE RoHS: | Yes |
| | |
| Physical Data | |
| Product Length (mm): | 65 |
| Product Depth (mm): | 30 |
| Product Width (mm): | 170 |
| Product Weight (g): | 320 |
| Optic: | Opal Polycarbonate diffuser |
| Material: | Die cast aluminium body with powder coated finish |
| Luminaire Fixing: | Wall Mounted |
| - | |
| Placement / Application: | Outdoor, General Lighting |
| | |

Electrical Data

| Power Consumption (w): | 8 |
|------------------------|--------------|
| Power Factor: | 0.4 |
| Amperage (mA): | 350 |
| Dimming: | Non-Dimmable |
| Driver Included: | Yes |
| Electric Current: | AC |

| EN: | | |
|----------------|--|--|
| LVD Certified: | | |


Light Data

| Luminous Flux in Lumens (Im): | 300 |
|--|---------------------|
| Luminous efficacy (Im/W): | 38 |
| Correlated Colour Temperature (CCT) (K): | 3000 |
| Colour Temperature Name: | Warm White |
| Colour Rendering Index (CRI): | 80 |
| Instant on (Less than 1 second): | Yes |
| LED Type: | Chip-on-board (COB) |
| Lifetime (hours): | 25000 |
| Switching Cycles: | 12500 |

EN-60598 Yes

Environment

| EN: | EN-60598 |
|-------------------------------------|----------|
| LVD Certified: | Yes |
| CE RoHS: | Yes |
| EU Luminaire: | L |
| Hg 0% (Mercury Free): | Yes |
| IP Rating (Ingress Protection): | IP54 |
| Lowest Operating Temperature (°C): | -20 |
| Maximum Operating Temperature (°C): | 50 |



Packaging

| Package Weight (g): | 345 |
|----------------------|------|
| Package Length (mm): | 75 |
| Package Width (mm): | 180 |
| Package Depth (mm): | 40 |
| Qty per euro pallet: | 1512 |

Portal.integral-led.com