

TARO TRIPLE 5650

SKU 1240019

astro



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|--------------------------|------------------------|--|
| FINISH: | Matt White | CABLE LENGTH: | Not Applicable |
| MAIN MATERIAL: | Metal - Aluminium | GROSS WEIGHT: | 0.70 (Kg) |
| DIMENSIONS: | H: 260mm W: 92mm D: 85mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Ceiling Mount | IP RATING: | IP20 |
| CUT OUT HOLE: | L: 235mm W: 80mm | BATHROOM ZONE: | Zone 3 |
| RECESS DEPTH: | 150 (mm) | VOLTAGE: | Mains 230 (V) |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Not suitable for mounting on flammable materials |


LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | GU10 | MACADAM ELLIPSE: | Not Applicable |
| MAXIMUM WATTAGE: | 3 x 50W Max | UGR: | To Be Advised |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE: | Lamp Dependant |
| LAMP INCLUDED? | No | TILT ADJUSTMENT ANGLE: | 30 (Degrees) |
| LUMINOUS FLUX: | Lamp Dependant | ROTATION ADJUSTMENT ANGLE: | 355 (Degrees) |
| COLOUR TEMP: | Lamp Dependant | AVERAGE LIFESPAN: | Lamp Dependant |
| CRI: | Lamp Dependant | L70: | Not Applicable |
| R9: | Lamp Dependant | | |

ELECTRICAL

| | | | |
|-------------------------------|----------------|-----------------------------------|----------------|
| SWITCHED: | No | SUPPLY FREQUENCY: | Not Applicable |
| DIMMABLE: | Yes | DRIVER / BALLAST VOLTAGE: | Not Applicable |
| DIMMING METHOD: | Lamp Dependant | DRIVER AVERAGE LIFESPAN: | Not Applicable |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | Lamp Dependant |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER / BALLAST INCLUDED? | Not Applicable |

ADDITIONAL INFORMATION



BOX QUANTITY x 20

PRODUCT ELEVATIONS

